

# 2005 PRODUCT GUIDE



PASSENGER AND LIGHT TRUCK

ULTRA HIGH PERFORMANCE PERFORMANCE & TOURING

LT & SUV PERFORMANCE LT & SUV LUXURY & COMFORT VAN WINTER

**Continental**<sup>®</sup>  
GERMAN ENGINEERED

# CONTISPORTCONTACT™ 2 VMAX

## UNPARALLELED SPEED AND PERFORMANCE

220 MPH SPEED RATING AND ENHANCED GRIP MAKE THIS THE WORLD'S FASTEST ROAD TIRE AND TIRE OF CHOICE FOR MANY OF EUROPE'S ULTRA SPORTS CARS.



<u>UTQG:</u>	<u>TREAD</u>	<u>TRACTION</u>	<u>TEMPERATURE</u>
ALL SIZES	280	AA	A

### FEATURES:

- Optimized profile design
- Additional siping and cooling grooves
- Rounder contours
- Stronger belt and cap ply material

### BENEFITS:

- Enhanced grip through reduced heat generation.
- Provide maximum transfer of heat away from the surface.
- Optimizes the stability of the tire at high speed.
- Increased control of the centrifugal forces that occur at high speeds.

	RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER	TIRE WEIGHT (KG)	TIRE WEIGHT (LB)	MAX. INFLATION PRESSURE	OVERALL SECTION WIDTH (MEASURING RIM)	APPROVED RIM WIDTHS	REVS PER MILE	TREAD DEPTH
19	35	235/35ZR19	Z	XL	BSW	03522800000	25.8	10.2	22.4	51	9.8 (8.5)	8.0 - 9.5	10/32	803	
		245/35ZR19	Z	XL	BSW	03522820000	25.7	10.5	23.1	51	9.5 (8.5)	8.0 - 9.5	10/32	806	
	30	275/30ZR19	Z	XL	BSW	03522830000	25.5	11.5	25.3	51	10.7 (9.5)	9.0 - 10.0	10/32	811	
		325/30ZR19	AVAILABLE MID 2005												
	25	315/25ZR19	Z	SL	BSW	03522810000	25.1	11.9	26.2	51	12.4 (11.0)	10.5 - 11.5	10/32	825	

NEW PRODUCT AVAILABLE SPRING 2005

CONTISPORTCONTACT™ 2 VMAX

ULTRA HIGH PERFORMANCE

PERFORMANCE & TOURING

LIGHT TRUCK & SUV PERFORMANCE

LIGHT TRUCK & SUV LUXURY & COMFORT

VAN

WINTER



# CONTISPORTCONTACT™ 2

ULTRA-HIGH PERFORMANCE FOR THE TRUE CAR ENTHUSIAST  
GERMAN INNOVATION PROVIDES PINPOINT HANDLING  
AND OUTSTANDING PERFORMANCE AT HIGH SPEEDS.



UTQG:	TREAD	TRACTION	TEMPERATURE
ALL SIZES	280	AA	A

## FEATURES:

- Bionic contour
- BiNet tread compound
- Stiff ribbed tread pattern

## BENEFITS:

- Precise steering and braking response by maintaining even footprint pressure.
- Provides optimum traction and handling on wet or dry surfaces.
- Maintains stable contact patch during braking and cornering for maximum control. Asymmetrical tread pattern that optimizes each side of the tread for excellent handling and outstanding traction.

	RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER	TIRE WEIGHT (KG)	TIRE WEIGHT (LB)	MAX. INFLATION PRESSURE	OVERALL SECTION WIDTH (MEASURING RIM)	APPROVED RIM WIDTHS	TREAD DEPTH	REVS PER MILE
16	60	215/60R16	95H	SL	BSW	03514070000	26.2	10.2	22.4	51	8.7 (6.5)	6.0 - 7.5	11/32	797	
	55	205/55R16	91V	SL	BSW	03521020000	24.9	9.3	20.4	51	8.4 (6.5)	5.5 - 7.5	10/32	837	
	50	205/50ZR16	Z	SL	BSW	03517800000	24.4	8.5	18.7	51	8.3 (6.5)	5.5 - 7.5	10/32	845	
		225/50R16	92V	SL	BSW	03522270000	24.7	9.5	20.9	51	9.1 (7.0)	6.0 - 8.0	10/32	833	
	45	205/45R16	83W	SL	BSW	03517830000	22.6	7.7	17.1	51	8.4 (7.0)	6.5 - 7.5	10/32	911	
		225/45ZR16	Z	SL	BSW	03516280000	24.0	8.8	19.4	51	9.1 (8.0)	7.5 - 9.0	10/32	856	
	40	195/40ZR16	80W	XL	BSW	03517900000	22.2	7.1	15.7	51	7.9 (7.0)	6.5 - 7.5	10/32	927	
		215/40ZR16	86W	XL	BSW	03516290000	22.6	8.1	17.8	51	8.6 (7.5)	7.0 - 8.5	10/32	911	
35	215/35ZR16	81W	XL	BSW	03518020000	21.9	7.9	17.4	51	8.5 (7.5)	7.0 - 8.5	10/32	940		
17	55	205/55ZR17	91Y	SL	BSW	03518790000	25.2	9.2	20.2	51	8.5 (6.5)	5.5 - 7.5	10/32	814	
		235/55R17	99W	SL	BSW	03520420000	27.2	10.5	23.1	51	9.6 (7.5)	6.5 - 8.5	10/32	767	
	50	205/50R17	93W	XL	BSW	03521760000	25.2	9.2	20.2	51	8.1 (6.5)	5.5 - 7.5	9/32	825	
		225/50R17	98Y	XL	BSW	03522920000	25.9	11.1	24.4	51	9.4 (7.0)	6.0 - 8.0	10/32	794	
		235/50ZR17	96Y	SL	BSW	03518800000	26.7	10.5	23.1	51	10.0 (7.5)	6.5 - 8.5	10/32	781	
		205/45ZR17	Z	XL	BSW	03517840000	24.0	9.1	20.0	51	8.4 (7.0)	6.5 - 7.5	10/32	856	
	45	215/45ZR17	Z	XL	BSW	03517850000	24.6	9.0	19.8	51	8.5 (7.0)	7.0 - 8.0	10/32	838	
		225/45R17	94W	XL	BSW	03512390000	25.0	9.2	20.3	51	8.9 (7.5)	7.0 - 8.5	10/32	828	
		225/45ZR17	91Y	SL	BSW	03523350000	25.0	9.7	21.4	51	8.9 (7.5)	7.0 - 8.5	10/32	835	
		235/45R17	97W	XL	BSW	03522720000	25.4	10.5	23.1	51	9.3 (8.0)	7.5 - 9.0	10/32	810	
		235/45R17	94Y	SL	BSW	03524520000	25.3	10.7	23.5	51	9.3 (8.0)	7.5 - 9.0	10/32	810	
		245/45R17	95W	SL	BSW	03525340000	25.7	10.9	23.9	51	9.6 (8.0)	7.0 - 9.0	10/32	812	
		245/45ZR17	99Y	XL	BSW	03516310000	25.7	11.3	24.9	51	9.8 (8.0)	7.5 - 9.0	10/32	811	
		195/40R17	81V	XL	BSW	03513870000	23.4	8.3	18.3	51	8.2 (7.5)	6.5 - 7.5	10/32	880	
	40	205/40ZR17	Z	XL	BSW	03517920000	23.3	8.4	18.4	51	8.6 (7.5)	7.0 - 8.0	10/32	883	
		215/40ZR17	87Y	XL	BSW	03516320000	23.9	8.6	18.9	51	8.8 (7.5)	7.0 - 8.5	10/32	859	
		235/40ZR17	Z	SL	BSW	03517930000	24.3	9.6	21.1	51	9.7 (8.5)	8.0 - 9.5	10/32	848	
		245/40R17	91W	SL	BSW	03521360000	24.7	10.1	22.3	51	9.8 (8.5)	8.0 - 9.5	10/32	842	
		255/40ZR17	Z	SL	BSW	03516330000	25.1	11.4	25.1	51	10.2 (9.0)	8.5 - 10.0	10/32	825	
	35	215/35R17	83V	XL	BSW	03518040000	23.0	8.0	17.7	51	8.6 (7.5)	7.0 - 8.5	9/32	895	
245/35ZR17		Z	SL	BSW	03516340000	23.8	9.2	20.3	51	9.5 (8.5)	8.0 - 9.5	10/32	862		
18	45	225/45R18	Z	SL	BSW	03524850000	26.0	11.0	24.2	51	8.9 (7.5)	7.0 - 8.5	10/32	803	
		235/45ZR18	98W	XL	BSW	03516450000	26.3	10.7	23.5	51	9.3 (8.0)	7.5 - 9.0	10/32	793	
		245/45ZR18	96Y	SL	BSW	03518480000	26.7	11.0	24.2	51	9.8 (8.0)	7.5 - 9.0	10/32	781	
		255/45R18	99Y	SL	BSW	03520440000	27.0	12.1	26.6	51	10.0 (8.5)	8.0 - 9.5	10/32	771	
		255/45R18	103Y	XL	BSW	03515150000	27.0	11.7	25.8	51	10.3 (8.5)	8.0 - 9.5	10/32	772	
	40	275/45R18	103Y	SL	BSW	03520450000	27.7	11.6	25.4	51	11.1 (9.5)	9.0 - 11.0	10/32	752	
		215/40ZR18	Z	XL	BSW	03517940000	24.8	10.0	22.0	51	8.6 (7.5)	7.0 - 8.5	10/32	830	
		225/40R18	88Y	SL	BSW	03520300000	25.1	9.7	21.3	51	8.9 (8.0)	7.5 - 9.0	9/32	825	
		225/40ZR18	Z	XL	BSW	03516350000	25.3	10.0	21.9	51	9.4 (8.0)	7.5 - 9.0	9/32	824	
		235/40R18	91Y	SL	BSW	03518500000	25.4	9.8	21.5	51	9.5 (8.5)	8.0 - 9.5	9/32	804	
		235/40ZR18	95Y	XL	BSW	03521160000	25.4	10.2	22.4	51	9.3 (8.5)	8.0 - 9.5	9/32	804	
		245/40R18	93Y	SL	BSW	03521370000	25.7	12.2	26.8	51	9.8 (8.5)	8.0 - 9.5	10/32	811	
		245/40R18	97Y	XL	BSW	03524470000	25.7	11.0	24.2	51	9.8 (8.5)	8.0 - 9.5	10/32	811	
		255/40R18	Z	SL	BSW	03524860000	26.0	11.0	24.2	51	10.2 (9.0)	8.5 - 10.0	10/32	801	
		265/40ZR18	101Y	XL	BSW	03516470000	26.4	11.2	24.6	51	11.2 (9.5)	9.0 - 10.5	10/32	779	
35	215/35ZR18	Z	XL	BSW	03518060000	24.1	9.5	20.9	51	8.6 (7.5)	7.0 - 8.5	10/32	853		

CONTI SPORTCONTACT™ 2

ULTRA HIGH PERFORMANCE

PERFORMANCE & TOURING

LIGHT TRUCK & SUV PERFORMANCE

LIGHT TRUCK & SUV LUXURY & COMFORT

VAN

WINTER

ULTRA HIGH PERFORMANCE

PERFORMANCE &amp; TOURING

LIGHT TRUCK &amp; SUV PERFORMANCE

LIGHT TRUCK &amp; SUV LUXURY &amp; COMFORT

VAN

WINTER

## CONTISPORTCONTACT™ 2

	RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER	TIRE WEIGHT (KG)	TIRE WEIGHT (LB)	MAX. INFLATION PRESSURE	OVERALL SECTION WIDTH (MEASURING RIM)	APPROVED RIM WIDTHS	TREAD DEPTH	REVS PER MILE
18	35	225/35ZR18	Z	XL	BSW	03516360000	24.1	9.1	20.0	51	9.2 (8.0)	7.5 - 9.0	9/32	853	
		245/35ZR18	92Y	XL	BSW	03518950000	24.8	10.7	23.5	51	9.8 (8.5)	8.0 - 9.5	10/32	830	
		255/35ZR18	94Y	XL	BSW	03518940000	25.0	10.9	24.0	51	10.0 (9.0)	8.5 - 10.0	10/32	828	
		265/35ZR18	Z	XL	BSW	03518230000	25.3	11.3	24.9	51	10.4 (9.5)	9.0 - 10.5	10/32	824	
		275/35ZR18	Z	SL	BSW	03516620000	25.4	11.4	25.1	51	11.2 (9.5)	9.0 - 11.0	10/32	810	
		295/35ZR18	99Y	SL	BSW	03521400000	24.3	14.2	31.2	51	10.6 (9.0)	10.0 - 11.0	10/32	847	
	30	255/30ZR18	Z	XL	BSW	03518130000	24.3	10.5	23.1	51	10.6 (9.0)	10.0 - 11.0	10/32	847	
		285/30ZR18	Z	SL	BSW	03515530000	24.8	11.4	25.1	51	11.5 (10.0)	9.5 - 10.5	10/32	834	
		295/30ZR18	Z	SL	BSW	03515360000	25.2	12.0	26.3	51	12.0 (10.5)	10.0 - 11.0	10/32	827	
19	45	245/45R19	98Y	SL	BSW	03522310000	27.8	12.5	27.4	51	10.0 (8.0)	7.5 - 9.0	10/32	740	
	40	225/40ZR19	Z	SL	BSW	03518670000	27.8	10.1	22.2	51	9.7 (8.0)	7.5 - 9.0	10/32	762	
		245/40ZR19	98Y	XL	BSW	03516040000	26.5	10.5	23.1	51	9.9 (8.5)	8.0 - 9.5	10/32	776	
		255/40R19	Z	SL	BSW	03524830000	27.0	17.0	37.4	51	10.2 (9.0)	8.5 - 10.0	10/32	762	
		255/40ZR19	Z	XL	BSW	03513200000	27.0	12.2	26.8	51	10.4 (9.0)	8.5 - 10.0	10/32	762	
		275/40R19	101Y	SL	BSW	03522320000	27.7	12.9	28.4	51	11.1 (9.5)	9.0 - 11.0	10/32	742	
	35	225/35ZR19	Z	XL	BSW	03518090000	25.1	10.2	22.4	51	9.1 (8.0)	7.5 - 9.0	10/32	825	
		235/35ZR19	Z	XL	BSW	03518620000	25.5	10.6	23.2	51	9.3 (8.5)	8.0 - 9.5	9/32	813	
		245/35R19	Z	XL	BSW	03514170000	25.8	10.8	23.7	51	9.8 (8.5)	8.0 - 9.5	10/32	813	
		255/35R19	92W	SL	BSW	03520630000	26.1	11.6	25.5	51	10.3 (9.0)	8.5 - 10.0	10/32	788	
		255/35ZR19	96Y	XL	BSW	03517440000	28.1	10.8	23.8	51	10.3 (9.0)	8.5 - 10.0	10/32	788	
		265/35ZR19	94Y	SL	BSW	03518440000	26.3	10.9	24.0	51	10.7 (9.5)	9.0 - 10.0	10/32	793	
		275/35ZR19	100Y	XL	BSW	03516050000	26.5	11.5	25.3	51	10.5 (9.5)	9.0 - 11.0	10/32	776	
		285/35ZR19	Z	SL	BSW	03521470000	26.9	13.8	30.4	51	11.4 (10.0)	9.0 - 11.0	10/32	776	
	30	255/30ZR19	Z	XL	BSW	03518140000	25.3	11.5	25.3	51	10.6 (9.0)	8.5 - 9.5	10/32	830	
		275/30R19	Z	XL	BSW	03514190000	25.5	11.4	25.1	51	11.1 (9.5)	9.0 - 11.0	10/32	818	
		295/30ZR19	Z	SL	BSW	03518200000	25.9	13.0	28.6	51	12.2 (10.5)	10.0 - 11.0	10/32	794	
		325/30ZR19	Z	XL	BSW	03525480000	26.7	12.5	27.5	51	12.8 (11.5)	11.0 - 12.0	8/32	782	
315/25ZR19		Z	SL	BSW	03520550000	25.1	11.1	24.4	51	12.4 (11.0)	10.5 - 11.5	10/32	825		
20	40	245/40ZR20	Z	SL	BSW	03516430000	27.8	11.6	25.5	51	9.7 (8.5)	8.0 - 9.5	10/32	750	
	35	245/35ZR20	Z	XL	BSW	03518120000	26.8	15.0	33.0	51	9.6 (8.5)	8.0 - 9.5	10/32	779	
		255/35ZR20	Z	XL	BSW	03526640000	27.0	12.0	26.4	51	10.2 (9.0)	8.5 - 10.0	10/32	771	
		275/35ZR20	102Y	XL	BSW	03522950000	27.6	11.9	26.2	51	11.0 (9.5)	9.0 - 11.0	10/32	756	
	30	235/30ZR20	Z	XL	BSW	03525490000	25.6	10.3	22.7	51	9.5 (8.5)	8.0 - 9.5	10/32	816	
		245/30ZR20	Z	XL	BSW	03521490000	25.9	13.7	30.1	51	9.6 (8.5)	8.0 - 9.5	10/32	805	
		255/30ZR20	Z	XL	BSW	03518540000	26.1	10.6	23.4	51	10.1 (9.0)	8.5 - 9.5	10/32	799	
		275/30ZR20	Z	XL	BSW	03518170000	26.5	12.0	26.4	51	10.4 (9.5)	9.0 - 10.0	10/32	787	
		285/25ZR20	Z	XL	BSW	03521500000	25.7	14.0	30.8	51	11.2 (10.5)	10.5 - 10.5	10/32	811	
305/25ZR20	Z	XL	BSW	03518550000	26.2	12.5	27.5	51	12.0 (11.0)	10.5 - 12.0	10/32	796			
21	30	255/30ZR21	Z	XL	BSW	03512460000	27.0	12.5	27.5	51	10.1 (9.0)	8.5 - 9.5	10/32	772	
		285/30R21	Z	XL	BSW	03516730000	27.7	13.0	28.6	51	11.2 (10.0)	9.5 - 10.5	10/32	752	
	25	295/25ZR21	Z	XL	BSW	03512380000	26.8	13.5	29.7	51	11.6 (10.5)	10.0 - 11.0	10/32	778	
22	30	265/30ZR22	Z	XL	BSW	03521280000	28.3	13.5	29.7	51	10.4 (9.5)	9.0 - 10.0	10/32	737	
	25	295/25ZR22	Z	XL	BSW	03521290000	27.8	14.6	32.1	51	11.6 (10.5)	10.0 - 11.0	10/32	749	

# SELF-SUPPORTING RUN FLAT TIRES

		RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER	TIRE WEIGHT (KG)	TIRE WEIGHT (LB)	MAX. INFLATION PRESSURE	OVERALL SECTION WIDTH (MEASURING RIM)	APPROVED RIM WIDTHS	TREAD DEPTH	REVS PER MILE
17	45	225/45R17	91Y	SL	BSW	03522600000	25.0	10.5	23.1	51	8.9 (7.5)	7.0 - 8.5	10/32	835		
		225/45R17	91W	SL	BSW	03520860000	25.0	11.4	25.1	51	8.9 (7.5)	7.0 - 8.5	10/32	835		
		225/45R17	91V	SL	BSW	03520850000	25.0	11.4	25.1	51	8.9 (7.5)	7.0 - 8.5	10/32	835		
	40	255/40R17	94Y	SL	BSW	03522630000	25.0	11.5	25.3	51	10.2 (9.0)	8.5 - 10.0	10/32	833		
		255/40R17	94W	SL	BSW	03522610000	25.0	11.5	25.3	51	10.2 (9.0)	8.5 - 10.0	10/32	833		
18	35	255/35R18	90W	SL	BSW	03522660000	25.0	11.7	25.7	51	10.2 (9.0)	8.0 - 10.0	10/32	833		

# ORIGINAL EQUIPMENT APPLICATIONS

Mercedes	16	55	205/55R16	91V	SL	BSW	03521020000	24.9	9.3	20.4	51	8.4 (6.5)	5.5 - 7.5	10/32	837	
Mercedes			205/55R16	91H	SL	BSW	03521030000	24.9	9.3	20.4	51	8.4 (6.5)	5.5 - 7.5	10/32	837	
Ford			205/55R16	91V	SL	BSW	03510610000	24.9	9.0	19.9	51	8.4 (6.5)	5.5 - 7.5	11/32	837	
Mercedes		50	225/50R16	92V	SL	BSW	03522270000	24.7	9.5	20.9	51	9.1 (7.0)	6.0 - 8.0	10/32	833	
Porsche	17	55	205/55ZR17	91Y	SL	BSW	03518790000	25.2	9.2	20.2	51	8.5 (6.5)	5.5 - 7.5	10/32	816	
Mercedes			235/55R17	99W	SL	BSW	03520420000	27.2	10.5	23.1	51	9.6 (7.5)	6.5 - 8.5	10/32	767	
Ford			205/50R17	93W	XL	BSW	03521760000	25.2	9.2	20.2	51	8.1 (6.5)	5.5 - 7.5	9/32	825	
Porsche		50	205/50ZR17	Z	SL	BSW	03515680000	25.2	9.3	20.4	51	8.5 (6.5)	5.5 - 7.5	9/32	827	
Volkswagen/Audi			225/50R17	98Y	XL	BSW	03522920000	25.9	11.1	24.4	51	9.4 (7.0)	6.0 - 8.0	10/32	867	
Porsche			235/50ZR17	96Y	SL	BSW	03518800000	26.7	10.5	23.1	51	10.0 (7.5)	6.5 - 8.5	10/32	781	
BMW			225/45R17	91Y	SL	BSW	03522600000	25.0	10.5	23.1	51	8.9 (7.5)	7.0 - 8.5	10/32	835	
SAAB		225/45R17	94W	XL	BSW	03512390000	25.0	9.2	20.3	51	8.9 (7.5)	7.0 - 8.5	10/32	828		
Mercedes		45	225/45R17	91W	SL	BSW	03521170000	25.0	9.7	21.4	51	8.9 (7.5)	7.0 - 8.5	10/32	835	
BMW			225/45R17	91W	SL	BSW	03520860000	25.0	11.4	25.1	51	8.9 (7.5)	7.0 - 8.5	10/32	835	
BMW			225/45R17	91V	SL	BSW	03520850000	25.0	11.400	25.1	51	8.9 (7.5)	7.0 - 8.5	10/32	835	
Volkswagen			225/45R17	91Y	SL	BSW	03517640000	25.0	9.3	20.5	51	8.9 (7.5)	7.0 - 8.5	10/32	835	
Mercedes			225/45ZR17	91Y	SL	BSW	03523350000	25.0	9.720	21.4	51	8.9 (7.5)	7.0 - 8.5	10/32	828	
Volkswagen			235/45R17	97W	XL	BSW	03522720000	25.4	10.5	23.1	51	9.3 (8.0)	7.5 - 9.0	10/32	851	
Mercedes			40	245/40R17	91W	SL	BSW	03521360000	24.7	10.1	22.3	51	9.8 (8.5)	8.0 - 9.5	10/32	842
Mercedes				245/40ZR17	91Y	SL	BSW	03523360000	24.8	10.1	22.2	51	9.8 (8.5)	8.0 - 9.5	10/32	834
BMW	255/40R17			94Y	SL	BSW	03522630000	25.0	11.5	25.3	51	10.2 (9.0)	8.5 - 10.0	10/32	833	
BMW	255/40R17			94W	SL	BSW	03522610000	25.0	11.5	25.3	51	10.2 (9.0)	8.5 - 10.0	10/32	833	
Porsche	255/40ZR17	Z		SL	BSW	03515690000	25.1	11.4	25.1	51	10.2 (9.0)	8.5 - 10.0	10/32	825		
BMW	18	45		225/45R18	Z	SL	BSW	03524850000	26.0	11.0	24.2	51	8.9 (7.5)	7.0 - 8.5	10/32	803
Mercedes			255/45R18	99Y	SL	BSW	03520440000	27.0	12.1	26.6	51	10.0 (8.5)	8.0 - 9.5	10/32	771	
Volkswagen			255/45R18	103Y	XL	BSW	03515150000	27.0	11.7	25.8	51	10.3 (8.5)	8.0 - 9.5	10/32	772	
Mercedes			275/45R18	103Y	SL	BSW	03520450000	27.7	11.6	25.4	51	11.1 (9.5)	9.0 - 11.0	10/32	752	
Audi		40	225/40R18	88Y	SL	BSW	03520300000	25.1	9.7	21.3	51	8.9 (8.0)	7.5 - 9.0	9/32	825	
Chrysler			225/40R18	92W	TL	BSW	03522490000	25.1	9.7	21.3	51	8.9 (8.0)	7.5 - 9.0	9/32	825	
Mercedes			225/40ZR18	92Y	XL	BSW	03518460000	25.1	9.6	21.2	51	8.9 (8.0)	7.5 - 9.0	9/32	826	
Porsche			225/40ZR18	Z	SL	BSW	03515340000	25.3	9.5	20.9	51	9.4 (8.0)	7.5 - 9.0	9/32	824	
Audi			235/40R18	91Y	SL	BSW	03518500000	25.4	9.8	21.5	51	9.5 (8.5)	8.0 - 9.5	9/32	804	
Porsche			235/40ZR18	91Y	SL	BSW	03518380000	25.6	9.9	21.8	51	9.8 (8.5)	8.0 - 9.5	9/32	804	
Jaguar			245/40R18	97Y	XL	BSW	03522670000	25.7	12.0	26.4	51	9.8 (8.5)	8.0 - 9.5	10/32	811	
Mercedes			245/40R18	93Y	SL	BSW	03521370000	25.7	12.2	26.8	51	9.8 (8.5)	8.0 - 9.5	10/32	811	
Mercedes			245/40R18	97Y	XL	BSW	03524470000	25.7	11.0	24.2	51	9.8 (8.5)	8.0 - 9.5	10/32	811	
Mercedes			245/40ZR18	Z	SL	BSW	03518220000	25.4	10.5	23.0	51	9.6 (8.5)	8.0 - 9.5	10/32	821	

CONTI SPORT CONTACT™ 2

ULTRA HIGH PERFORMANCE

PERFORMANCE & TOURING

LIGHT TRUCK & SUV PERFORMANCE

LIGHT TRUCK & SUV LUXURY & COMFORT

VAN

WINTER

ORIGINAL EQUIPMENT APPLICATIONS

CONTISPORTCONTACT™ 2

		RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER	TIRE WEIGHT	TIRE WEIGHT (KG)	MAX. INFLATION PRESSURE	OVERALL SECTION WIDTH (MEASURING RIM)	APPROVED RIM WIDTHS	TREAD DEPTH	REVS PER MILE		
BMW	18	40	255/40R18	Z	SL	BSW	03524860000	26.0	11.0	24.2	51	10.2 (9.0)	8.5 - 10.0	10/32	801			
Porsche			265/40ZR18	101Y	XL	BSW	03516470000	26.4	11.2	24.6	51	11.2 (9.5)	9.0 - 10.5	10/32	779			
Mercedes		35	245/35ZR18	92Y	XL	BSW	03518950000	24.8	10.7	23.5	51	9.8 (8.5)	8.0 - 9.5	10/32	830			
BMW			255/35R18	90W	SL	BSW	03522660000	25.0	11.7	25.7	51	10.2 (9.0)	8.0 - 10.0	10/32	833			
Mercedes			255/35ZR18	94Y	XL	BSW	03518940000	25.0	10.9	24.0	51	10.0 (9.0)	8.5 - 10.0	10/32	828			
Mercedes			265/35R18	97Y	XL	BSW	03524430000	25.3	11.2	24.6	51	10.7 (9.5)	9.0 - 10.0	10/32	824			
Mercedes			265/35ZR18	Z	XL	BSW	03518230000	25.3	11.3	24.9	51	10.4 (9.5)	9.0 - 10.5	10/32	824			
Porsche			265/35ZR18	Z	SL	BSW	03515350000	25.2	11.2	24.6	51	11.1 (9.5)	9.0 - 10.0	10/32	827			
Jaguar			275/35R18	99Y	XL	BSW	03522680000	25.6	12.5	27.5	51	11.0 (9.5)	9.0 - 11.0	10/32	810			
Mercedes			275/35R18	95Y	SL	BSW	03521390000	25.4	13.1	28.8	51	11.2 (9.5)	9.0 - 11.0	10/32	810			
Porsche			30	285/30ZR18	Z	SL	BSW	03515530000	24.8	11.4	25.1	51	11.5 (10.0)	9.5 - 10.5	10/32	834		
Porsche				295/30ZR18	Z	SL	BSW	03515360000	25.2	12.0	26.3	51	12.0 (10.5)	10.0 - 11.0	10/32	827		
BMW			19	45	245/45R19	98Y	SL	BSW	03522310000	27.8	12.5	27.4	51	10.0 (8.0)	7.5 - 9.0	10/32	740	
BMW					40	225/40ZR19	Z	SL	BSW	03518670000	27.8	10.1	22.2	51	9.7 (8.0)	7.5 - 9.0	10/32	762
Mercedes	255/40R19	Z		SL		BSW	03524830000	27.0	17.0	37.4	51	10.2 (9.0)	8.5 - 10.0	10/32	771			
Mercedes	255/40R19	96Y		SL		BSW	03520460000	27.0	12.0	26.5	51	10.2 (9.0)	8.5 - 10.0	10/32	762			
BMW	255/40ZR19	Z		SL		BSW	03521460000	27.0	12.2	26.8	51	10.2 (9.0)	8.5 - 10.0	10/32	762			
Audi	255/40ZR19	Z		XL		BSW	03513200000	27.0	12.2	26.8	51	10.4 (9.0)	8.5 - 10.0	10/32	762			
BMW	275/40R19	101Y		SL		BSW	03522320000	27.7	12.9	28.4	51	11.1 (9.5)	9.0 - 11.0	10/32	927			
Mercedes	275/40R19	101Y		SL		BSW	03520470000	27.7	12.3	27.1	51	11.1 (9.5)	9.0 - 11.0	10/32	742			
Porsche	35	235/35ZR19		87Y		SL	BSW	03516680000	25.3	10.3	22.7	51	9.3 (8.5)	8.0 - 9.5	10/32	813		
Mercedes		245/35R19		Z		XL	BSW	03514170000	25.8	10.8	23.7	51	9.8 (8.5)	8.0 - 9.5	10/32	813		
Chrysler		255/35R19		92W		SL	BSW	03520630000	26.1	11.6	25.5	51	10.3 (9.0)	8.5 - 10.0	10/32	788		
Volkswagen/Audi		255/35ZR19		96Y		XL	BSW	03517440000	28.1	10.8	23.8	51	10.3 (9.0)	8.5 - 10.0	10/32	788		
Porsche		265/35ZR19		94Y		SL	BSW	03518440000	26.3	10.9	24.0	51	10.7 (9.5)	9.0 - 10.0	10/32	793		
BMW		285/35ZR19		Z		SL	BSW	03521470000	26.9	13.8	30.4	51	11.4 (10.0)	9.0 - 11.0	10/32	776		
Mercedes		30		275/30R19		Z	XL	BSW	03514190000	25.5	11.4	25.1	51	11.1 (9.5)	9.0 - 11.0	10/32	818	
Porsche				295/30ZR19		100Y	XL	BSW	03516690000	25.9	13.0	28.6	51	12.2 (10.5)	10.0 - 11.0	10/32	794	
Porsche				25		315/25ZR19	Z	SL	BSW	03520550000	25.1	11.1	24.4	51	12.4 (11.0)	10.5 - 11.5	10/32	825
Mercedes						20	275/35ZR20	Z	XL	BSW	03526650000	27.6	15.6	34.3	51	11.1 (9.5)	9.0 - 11.0	10/32
Volkswagen/Audi	275/35ZR20	102Y		XL			BSW	03522950000	27.6	11.9	26.2	51	11.0 (9.5)	9.0 - 11.0	10/32	756		
Porsche	305/25ZR20	Z		XL	BSW		03518550000	26.2	12.5	27.5	51	12.0 (11.0)	10.5 - 12.0	10/32	796			

ULTRA HIGH PERFORMANCE

PERFORMANCE & TOURING

LIGHT TRUCK & SUV PERFORMANCE

LIGHT TRUCK & SUV LUXURY & COMFORT

VAN

WINTER



# CONTISPORTCONTACT™

## DESIGNED FOR PERFORMANCE AND CONTROL

SUPERB CORNERING STABILITY AND PRECISION STEERING RESPONSE ARE WHY THIS TIRE IS ORIGINAL EQUIPMENT ON MANY OF THE WORLD'S ELITE VEHICLES.



UTQG:	TREAD	TRACTION	TEMPERATURE
ALL SIZES	280	A	A

### FEATURES:

- Asymmetrical tread pattern
- Open tread shoulder grooves
- Solid center steering rib

### BENEFITS:

- Superb cornering stability and precision steering response.
- Outstanding grip on wet surfaces and reduced hydroplaning.
- Excellent straight-line stability and smooth quiet ride.

		RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER	TIRE WEIGHT (KG)	TIRE WEIGHT (LB)	MAX. INFLATION PRESSURE	OVERALL SECTION WIDTH (MEASURING RIM)	APPROVED RIM WIDTHS	TREAD DEPTH	REVS PER MILE
16	55	205/55R16	91W	SL	BSW	03513960000	24.9	9.2	20.3	51	8.4 (6.5)	5.5 - 7.5	10/32	831		
		205/55R16	91W	SL	BSW	03513770000	24.9	9.5	21.0	51	8.4 (6.5)	5.5 - 7.5	10/32	831		
	50	195/50R16	88H	XL	BSW	03518290000	23.7	9.1	20.0	51	8.5 (6.0)	5.5 - 7.0	10/32	864		
		195/50R16	84H	SL	BSW	03514020000	23.7	7.3	16.1	44	8.5 (6.0)	5.5 - 7.0	10/32	864		
		205/50R16	87V	SL	BSW	03513840000	24.1	8.8	19.4	44	8.4 (6.5)	5.5 - 7.5	10/32	853		
		225/50ZR16	92W	SL	BSW	03514270000	25.2	9.9	21.7	51	9.2 (7.0)	6.0 - 8.0	10/32	827		
	45	195/45R16	80V	SL	BSW	03515400000	22.9	7.7	17.0	51	7.7 (6.5)	6.0 - 7.5	10/32	893		
		245/45ZR16	Z	SL	BSW	03514300000	24.6	11.0	24.1	44	9.6 (8.0)	7.5 - 9.0	10/32	839		
	17	55	225/55R17	97W	SL	BSW	03514430000	26.8	11.5	25.3	44	9.2 (7.0)	6.0 - 8.0	10/32	778	
		50	205/50R17	93W	XL	BSW	03515260000	25.1	9.7	21.4	51	8.4 (6.5)	5.5 - 7.5	10/32	825	
45		225/45R17	94W	XL	BSW	03520350000	24.9	9.8	21.5	51	8.9 (7.5)	7.0 - 8.5	10/32	831		
		225/45R17	91W	SL	BSW	03514500000	25.7	9.8	21.6	51	8.9 (7.5)	7.0 - 8.5	10/32	811		
40		235/45R17	94Y	SL	BSW	03514570000	25.7	10.6	23.3	51	9.6 (8.0)	7.5 - 9.0	10/32	811		
		255/45R17	98W	SL	BSW	03515550000	26.2	11.7	25.7	51	10.2 (8.5)	8.0 - 9.5	10/32	796		
35		215/40ZR17	Z	XL	BSW	03516830000	24.1	8.5	18.7	51	8.6 (7.5)	7.0 - 8.5	10/32	853		
		245/40ZR17	Z	SL	BSW	03525080000	25.0	10.7	23.5	51	10.0 (8.5)	8.0 - 9.5	10/32	828		
35		255/40R17	94Y	SL	BSW	03515750000	25.0	10.6	23.4	51	10.2 (9.0)	8.5 - 10.0	10/32	833		
		225/35ZR17	Z	RF	BSW	03514660000	23.5	7.7	17.0	51	9.2 (8.0)	7.5 - 9.0	10/32	870		
18	50	235/50ZR18	Z	SL	BSW	03524400000	27.0	11.4	25.1	51	9.7 (7.5)	6.5 - 8.5	10/32	772		
	45	225/45ZR18	Z	SL	BSW	03514820000	25.9	10.4	22.8	51	8.9 (7.5)	7.0 - 8.5	10/32	805		
		245/45ZR18	96W	SL	BSW	03515760000	26.7	11.6	25.4	51	9.6 (8.0)	7.5 - 9.0	10/32	781		
		255/45ZR18	99W	SL	BSW	03515780000	27.1	12.2	26.8	51	10.0 (8.5)	8.0 - 9.5	10/32	769		
		255/45ZR18	Z	SL	BSW	03514740000	27.1	11.9	26.2	51	10.2 (8.5)	8.0 - 9.5	10/32	769		
40	255/40ZR18	Z	SL	BSW	03514830000	26.0	11.2	24.7	51	10.2 (9.0)	8.5 - 10.0	10/32	802			
19	40	225/40ZR19	Z	SL	BSW	03516510000	26.1	10.4	22.9	51	9.1 (8.0)	7.5 - 9.0	10/32	799		
	35	255/35ZR19	Z	SL	BSW	03516520000	26.0	10.8	23.7	51	10.2 (9.0)	8.5 - 10.0	10/32	802		

**ORIGINAL EQUIPMENT APPLICATIONS**

BMW	16	55	205/55R16	91W	SL	BSW	03513960000	24.9	9.2	20.3	51	8.4 (6.5)	5.5 - 7.5	10/32	831	
BMW			205/55R16	91V	SL	BSW	03513900000	24.9	9.2	20.3	51	8.4 (6.5)	5.5 - 7.5	10/32	831	
Volvo		50	205/55R16	91W	SL	BSW	03513780000	24.9	9.5	21.0	51	10.1 (6.5)	5.5 - 7.5	10/32	831	
Volkswagen			205/55R16	91W	SL	BSW	03513770000	24.9	9.5	21.0	51	8.4 (6.5)	5.5 - 7.5	10/32	831	
Mercedes			195/50R16	88H	XL	BSW	03518290000	23.7	9.1	20.0	51	8.5 (6.0)	5.5 - 7.0	10/32	864	
Mercedes			195/50R16	84H	SL	BSW	03514020000	23.7	7.3	16.1	44	8.5 (6.0)	5.5 - 7.0	10/32	864	
Ford		45	205/50R16	87V	SL	BSW	03513840000	24.1	8.8	19.4	44	8.4 (6.5)	5.5 - 7.5	10/32	853	
Porsche			225/50ZR16	Z	SL	BSW	03527950000	25.0	11.0	24.2	44	10.1 (7.0)	6.0 - 8.0	10/32	828	
BMW		17	55	225/50ZR16	92W	SL	BSW	03514270000	25.2	9.9	21.7	51	9.2 (7.0)	6.0 - 8.0	10/32	827
Porsche				245/45ZR16	Z	SL	BSW	03514300000	24.6	11.0	24.1	44	9.6 (8.0)	7.5 - 9.0	10/32	839
Mercedes	50		225/55R17	97W	SL	BSW	03514430000	26.8	11.5	25.3	44	9.2 (7.0)	6.0 - 8.0	10/32	778	
BMW			205/50R17	93W	XL	BSW	03515260000	25.1	9.7	21.4	51	8.4 (6.5)	5.5 - 7.5	10/32	825	
Jaguar			225/45R17	94W	XL	BSW	03520350000	24.9	9.8	21.5	51	8.9 (7.5)	7.0 - 8.5	10/32	831	
Volvo			225/45R17	91W	SL	BSW	03515770000	24.9	9.8	21.5	51	8.9 (7.5)	7.0 - 8.5	10/32	831	
BMW	45		225/45R17	91W	SL	BSW	03514500000	25.7	9.8	21.6	51	8.9 (7.5)	7.0 - 8.5	10/32	811	
BMW			225/45ZR17	Z	SL	BSW	03514510000	25.2	10.1	22.3	51	8.9 (7.5)	7.0 - 8.5	10/32	827	
Mercedes	40		235/45R17	94W	SL	BSW	03514600000	25.3	10.3	22.6	51	9.5 (8.0)	7.5 - 9.0	10/32	824	
BMW			235/45R17	94Y	SL	BSW	03514570000	25.7	10.6	23.3	51	9.6 (8.0)	7.5 - 9.0	10/32	811	
Mercedes	35	255/45R17	98W	SL	BSW	03515550000	26.2	11.7	25.7	51	10.2 (8.5)	8.0 - 9.5	10/32	796		
Ford		215/40ZR17	Z	XL	BSW	03516830000	24.1	8.5	18.7	51	8.6 (7.5)	7.0 - 8.5	10/32	853		
BMW	18	40	245/40ZR17	Z	SL	BSW	03525080000	25.0	10.7	23.5	51	10.0 (8.5)	8.0 - 9.5	10/32	828	
Audi			255/40R17	94Y	SL	BSW	03515750000	25.0	10.6	23.4	51	10.2 (9.0)	8.5 - 10.0	10/32	833	
BMW		45	235/50ZR18	Z	SL	BSW	03524400000	27.0	11.4	25.1	51	9.7 (7.5)	6.5 - 8.5	10/32	772	
BMW/Toyota			225/45ZR18	Z	SL	BSW	03514820000	25.9	10.4	22.8	51	8.9 (7.5)	7.0 - 8.5	10/32	805	
Jaguar			245/45ZR18	96W	SL	BSW	03515760000	26.7	11.6	25.4	51	9.6 (8.0)	7.5 - 9.0	10/32	781	
Jaguar	40	255/45ZR18	99W	SL	BSW	03515780000	27.1	12.2	26.8	51	10.0 (8.5)	8.0 - 9.5	10/32	769		
Mercedes/BMW		255/45ZR18	Z	SL	BSW	03514740000	27.1	11.9	26.2	51	10.2 (8.5)	8.0 - 9.5	10/32	769		
BMW	19	40	225/40ZR19	Z	SL	BSW	03516510000	26.1	10.4	22.9	51	9.1 (8.0)	7.5 - 9.0	10/32	799	
BMW		35	255/35ZR19	Z	SL	BSW	03516520000	26.0	10.8	23.7	51	10.2 (9.0)	8.5 - 10.0	10/32	802	

ULTRA HIGH PERFORMANCE

PERFORMANCE & TOURING

LIGHT TRUCK & SUV PERFORMANCE

LIGHT TRUCK & SUV LUXURY & COMFORT

VAN

WINTER

# CONTIEXTREMECONTACT™

## ABSOLUTE RESPONSIVENESS AND PERFORMANCE IN ALL-SEASON CONDITIONS

DIRECTIONAL TREAD DESIGN PROVIDES OPTIMUM  
AGILITY, STABILITY AND TRACTION IN WET, DRY  
AND SNOWY CONDITIONS.



UTQG:	TREAD	TRACTION	TEMPERATURE
V RATED	400	A	A
W RATED	400	AA	A

### FEATURES:

- Shark Fin bio-mechanic™ directional tread design
- TriNet, silica-based, tread compound
- Spiral-wound jointless nylon cap piles
- Bionic contour

### BENEFITS:

- Provides optimum agility, stability, speed and performance in all-season conditions. Provides water evacuation routes for hydroplaning resistance.
- Superb handling and traction in wet, dry, and snow conditions. Improved tread life.
- Superior uniformity and high speed integrity.
- Precise steering and braking response by maintaining even footprint pressure under all conditions.

# CONTIEXTREMECONTACT™

	RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER	TIRE WEIGHT (KG)	TIRE WEIGHT (LB)	MAX. INFLATION PRESSURE	OVERALL SECTION WIDTH (MEASURING RIM)	APPROVED RIM WIDTHS	TREAD DEPTH	REVS PER MILE
15	65	P205/65R15		92V	SL	BSW	15471290000	25.5	11.2	24.6	44	8.2 (6.0)	5.5 - 7.5	10/32	818
	60	P225/60R15		95V	SL	BSW	15471350000	25.6	11.0	24.2	44	9.0 (6.5)	6.0 - 8.0	10/32	814
	55	P205/55R15		87V	SL	BSW	15471300000	23.9	9.7	21.3	44	8.4 (6.5)	5.5 - 7.5	10/32	859
16	60	P215/60R16		94V	SL	BSW	15471410000	26.1	11.6	25.4	44	8.7 (6.5)	6.0 - 7.5	10/32	799
		P225/60R16		97V	SL	BSW	15471220000	26.6	12.3	27.1	44	9.0 (6.5)	6.0 - 8.0	10/32	784
		P205/55R16		89V	SL	BSW	15471250000	24.9	10.2	22.3	44	8.4 (6.5)	5.5 - 7.5	10/32	831
	55	P215/55R16		91V	SL	BSW	15471380000	25.3	11.4	25.1	44	8.9 (7.0)	6.0 - 7.5	10/32	824
		P225/55R16		94V	SL	BSW	15471270000	25.8	11.7	25.7	44	9.2 (7.0)	6.0 - 8.0	10/32	808
		P225/50R16		91V	SL	BSW	15471230000	24.9	11.4	25.1	44	9.2 (7.0)	6.0 - 8.0	10/32	831
50	P245/50R16		96V	SL	BSW	15471280000	25.7	12.5	27.4	44	10.0 (7.5)	7.0 - 8.5	10/32	811	
17	50	P215/50ZR17		90W	SL	BSW	15471390000	25.5	10.9	24.0	44	8.9 (7.0)	6.0 - 7.5	10/32	818
		P255/50ZR17		100W	SL	BSW	15471370000	27.1	13.6	30.0	44	10.4 (8.0)	7.0 - 9.0	10/32	769
		P215/45ZR17		87W	SL	BSW	15471360000	24.7	10.1	22.2	44	8.4 (7.0)	7.0 - 8.0	10/32	836
	45	P225/45ZR17		90W	SL	BSW	15471340000	25.0	10.6	23.3	44	8.9 (7.5)	7.0 - 8.5	10/32	828
		P235/45ZR17		93W	SL	BSW	15471320000	25.4	10.9	24.1	44	9.3 (8.0)	7.5 - 9.0	10/32	821
		P245/45ZR17		95W	SL	BSW	15471260000	25.7	12.0	26.4	44	9.6 (8.0)	7.0 - 9.0	10/32	812
	40	P205/40ZR17		80W	SL	BSW	15471310000	23.5	9.3	20.4	44	8.4 (7.5)	7.0 - 8.0	10/32	870
		P215/40ZR17		83W	SL	BSW	15471400000	23.8	9.7	21.2	44	8.6 (7.5)	7.0 - 8.5	10/32	862
		P255/40ZR17		94W	SL	BSW	15471420000	25.0	11.8	25.9	44	10.2 (9.0)	8.5 - 10.0	10/32	828
P275/40ZR17			98W	SL	BSW	15471330000	25.7	14.7	32.3	44	10.9 (9.5)	9.0 - 11.0	10/32	811	
18	45	P245/45ZR18		96W	SL	BSW	15471480000	26.7	12.4	27.3	44	9.6 (8.0)	7.5 - 9.0	10/32	791
		P225/40ZR18		88W	SL	BSW	15471210000	25.1	10.9	24.0	44	9.1 (8.0)	7.5 - 9.0	10/32	831
		P235/40ZR18		90W	SL	BSW	15471440000	25.4	11.3	24.9	44	9.5 (8.5)	8.0 - 9.5	10/32	821
	40	P245/40ZR18		93W	SL	BSW	15471430000	25.7	11.6	25.5	44	9.8 (8.5)	8.0 - 9.5	10/32	811
		P255/40ZR18		95W	SL	BSW	15471490000	26.0	12.4	27.3	44	10.2 (9.0)	8.5 - 10.0	10/32	802
		P275/40ZR18		99W	SL	BSW	15471470000	26.7	13.1	28.9	44	10.9 (9.5)	9.0 - 11.0	10/32	781
35	P215/35ZR18		80W	SL	BSW	15471460000	23.9	8.6	18.9	44	8.6 (7.5)	7.0 - 8.5	10/32	859	
20	35	P255/35ZR20		93W	SL	BSW	15471450000	27.0	11.9	26.2	44	10.0 (9.0)	8.5 - 10.0	10/32	772

ULTRA HIGH PERFORMANCE

PERFORMANCE & TOURING

LIGHT TRUCK & SUV PERFORMANCE

LIGHT TRUCK & SUV LUXURY & COMFORT

VAN

WINTER



# CONTIProCONTACT™

## ALL-SEASON, ALL-CONDITION VERSATILITY

UNPARALLELED WET-BRAKING CAPACITY AND YEAR-ROUND TRACTION GIVE THIS TIRE OUTSTANDING HANDLING, CONTROL AND HIGH-SPEED CAPABILITIES.



UTQG:	TREAD	TRACTION	TEMPERATURE
ALL SIZES	400	AA	A

### FEATURES:

- Straight circumferential grooves for greater water evacuation
- Central rib with alternating convex and concave sipe design
- Optimized shoulder lug stability
- Optimized sipes with defined radius create an interlocking effect
- All season tire

### BENEFITS:

- Outstanding braking on wet surfaces.
- Reduced tread pattern noise level.
- Enhanced handling and steering response.
- Improved stability and enhanced dry performance.
- Controlled driving performance for every condition.

ULTRA HIGH PERFORMANCE

PERFORMANCE & TOURING

LIGHT TRUCK & SUV PERFORMANCE

LIGHT TRUCK & SUV LUXURY & COMFORT

VAN

WINTER

		RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER	TIRE WEIGHT (KG)	TIRE WEIGHT (LB)	MAX. INFLATION PRESSURE	OVERALL SECTION WIDTH (MEASURING RIM)	APPROVED RIM WIDTHS	TREAD DEPTH	REVS PER MILE
15	65	185/65R15	88H	SL	BSW	15476700000	24.5	8.8	19.4	51	7.4 (5.5)	5.0 - 6.5	10/32	849		
		195/65R15	91H	SL	BSW	03522090000	25.0	8.0	17.7	51	7.9 (6.0)	5.0 - 7.0	10/32	835		
		205/65R15	94H	SL	BSW	15476710000	25.5	9.9	21.8	51	8.2 (6.0)	5.0 - 7.5	10/32	818		
	60	195/60R15	88H	SL	BSW	15476720000	24.2	9.0	19.7	51	7.9 (6.0)	5.0 - 7.0	10/32	856		
		205/60R15	91H	SL	BSW	15476730000	24.7	9.4	20.6	51	8.2 (6.0)	5.5 - 7.5	10/32	843		
16	60	225/60R16	98H	SL	BSW	15476740000	26.6	11.7	25.8	51	9.0 (6.5)	6.0 - 8.0	10/32	783		
		235/60R16	100H	SL	BSW	15476750000	27.1	13.4	29.5	51	9.4 (7.0)	6.5 - 8.5	10/32	769		
	55	205/55R16	91H	SL	BSW	03521300000	24.9	10.2	22.3	51	8.4 (6.5)	5.5 - 7.5	10/32	837		
		215/55R16	93H	SL	BSW	15476760000	25.3	10.6	23.2	51	8.9 (7.0)	6.0 - 7.5	10/32	824		
		215/55R16	97H	XL	BSW	03522710000	25.3	10.0	22.0	51	8.9 (7.0)	6.0 - 7.5	10/32	824		
		225/55R16	99H	XL	BSW	03522070000	25.7	9.5	20.9	51	9.1 (7.0)	6.0 - 8.0	10/32	810		
17	55	235/55R17	99H	SL	BSW	03521270000	27.2	10.5	23.1	51	9.6 (7.5)	6.5 - 8.5	10/32	767		
		205/50R17	93V	SL	BSW	15476770000	25.1	9.9	21.8	51	8.4 (6.5)	5.5 - 7.5	10/32	832		
	50	215/50R17	91H	SL	BSW	15476780000	25.5	11.0	24.3	51	8.9 (7.0)	6.0 - 7.5	10/32	819		
		225/50R17	94V	SL	BSW	03520360000	25.9	10.4	22.9	51	9.2 (7.0)	6.0 - 8.0	10/32	806		
	45	225/45R17	91H	SL	BSW	03522460000	25.0	10.0	22.0	51	8.9 (7.5)	7.0 - 8.5	10/32	835		
		235/45R17	97H	XL	BSW	03522790000	25.3	10.5	23.1	51	9.3 (8.0)	7.5 - 9.0	10/32	823		
		235/45R17	94H	SL	BSW	03521310000	25.3	10.5	23.1	51	9.3 (8.0)	7.5 - 9.0	10/32	823		
		245/45R17	99H	XL	BSW	03521320000	25.7	10.8	23.7	51	9.6 (8.0)	7.0 - 9.0	10/32	812		
18	50	235/50R18	97H	SL	BSW	03522940000	27.3	11.4	25.1	51	9.7 (7.5)	6.5 - 8.5	10/32	765		
		245/45R18	96H	SL	BSW	15476790000	26.7	11.0	24.2	51	9.6 (8.0)	7.5 - 9.0	10/32	782		
	45	255/45R18	99H	SL	BSW	03524820000	27.0	11.7	25.8	51	10.0 (8.5)	8.0 - 9.5	10/32	771		
		245/40R18	93H	SL	BSW	03522260000	25.7	13.0	28.6	51	9.8 (8.5)	8.0 - 9.5	10/32	811		
		245/40R18	97H	XL	BSW	03522200000	25.7	10.6	23.3	51	9.8 (8.5)	8.0 - 9.5	10/32	811		

**SELF-SUPPORTING RUN FLAT TIRES**

16	55	205/55R16	91H	SL	BSW	03523100000	24.9	10.2	22.3	51	8.4 (6.5)	5.5 - 7.5	10/32	837
		205/55R16	91V	SL	BSW	03520780000	24.9	10.1	22.2	51	8.4 (6.5)	5.5 - 7.5	10/32	837
17	50	225/50R17	94V	SL	BSW	03523400000	25.9	11.7	25.7	51	9.2 (7.0)	6.0 - 8.0	10/32	806
		225/45R17	91V	SL	BSW	03522590000	25.0	11.4	25.1	51	8.9 (7.5)	7.0 - 8.5	10/32	835

**ORIGINAL EQUIPMENT APPLICATIONS**

Volkswagen	15	65	195/65R15	91H	SL	BSW	03522090000	25.0	8.0	17.7	51	7.91 (6.0)	5 - 7	10/32	835
Volkswagen	16	55	205/55R16	91H	SL	BSW	03523100000	24.9	10.2	22.3	51	8.4 (6.5)	5.5 - 7.5	10/32	837
Volkswagen			205/55R16	91H	SL	BSW	03522770000	24.9	9.1	20.0	51	8.4 (6.5)	5.5 - 7.5	10/32	837
Mercedes			205/55R16	91H	SL	BSW	03521300000	24.9	10.2	22.3	51	8.4 (6.5)	5.5 - 7.5	10/32	837
BMW			205/55R16	91V	SL	BSW	03520780000	24.9	10.1	22.2	51	8.4 (6.5)	5.5 - 7.5	10/32	837
Audi			215/55R16	97H	XL	BSW	03522710000	25.3	10.0	22.0	51	8.9 (7.0)	6 - 7.5	10/32	824
Audi			225/55R16	99H	XL	BSW	03522070000	25.7	9.5	20.9	51	9.1 (7.0)	6 - 8	10/32	810
BMW			225/55R16	95V	SL	BSW	03518660000	25.7	9.8	21.6	51	9.1 (7.0)	6 - 8	10/32	810
Mercedes			17	55	235/55R17	99H	SL	BSW	03521270000	27.2	10.5	23.1	51	9.6 (7.5)	6.5 - 8.5
BMW	225/50R17	94W			SL	BSW	03524810000	25.9	11.2	24.6	51	9.17 (7.0)	6 - 8	10/32	806
BMW	50	225/50R17		94V	SL	BSW	03523400000	25.9	11.7	25.7	51	9.17 (7.0)	6 - 8	10/32	806
BMW		225/50R17		94V	SL	BSW	03520360000	25.9	10.4	22.9	51	9.17 (7.0)	6 - 8	10/32	806
BMW	45	225/45R17		91V	SL	BSW	03522590000	25.0	11.4	25.1	51	8.9 (7.5)	7 - 8.5	10/32	835
Volkswagen		225/45R17		91H	SL	BSW	03522460000	25.0	10.0	22.0	51	8.9 (7.5)	7 - 8.5	10/32	835
Volkswagen		235/45R17		97H	XL	BSW	03522790000	25.3	10.5	23.1	51	9.3 (8.0)	7.5 - 9	10/32	823
Audi		235/45R17		94H	SL	BSW	03521310000	25.3	10.5	23.1	51	9.3 (8.0)	7.5 - 9	10/32	823
Audi	245/45R17	99H		XL	BSW	03521320000	25.7	10.8	23.7	51	9.6 (8.0)	7 - 9	10/32	812	
Jaguar	18	50		235/50R18	97H	SL	BSW	03522940000	27.3	11.4	25.1	51	9.65 (7.5)	6.5 - 8.5	10/32
Audi			255/45R18	99H	SL	BSW	03524820000	27.0	11.7	25.8	51	10 (8.5)	8 - 9.5	10/32	771
Jaguar		40	245/40R18	93H	SL	BSW	03522260000	25.7	13.0	28.6	51	9.8 (8.5)	8 - 9.5	10/32	811
Audi			245/40R18	97H	XL	BSW	03522200000	25.7	10.6	23.3	51	9.8 (8.5)	8 - 9.5	10/32	811



# CONTITOURINGCONTACT™ CT/CH/CV/CW95

## PERFECT FOR PERFORMANCE TOURING CARS

THIS INNOVATIVE TIRE OFFERS A SMOOTH, LOW-NOISE RIDE AND REDUCED ROLLING RESISTANCE FOR OPTIMIZED FUEL EFFICIENCY.



UTQG:	TREAD	TRACTION	TEMPERATURE
ALL SIZES	360	A	A

6	0	0	0	0	MILE LIMITED TREADWEAR WARRANTY
---	---	---	---	---	---------------------------------

96,000 KM

### FEATURES:

- Proven Original Equipment Fitments
- Tri-radial tread contour
- Weight-optimized construction
- Spiral-wound, jointless nylon cap piles

### BENEFITS:

- Selected tire by many major European automobile manufacturers.
- Provides better wear, quieter ride, and greater resistance to hydroplaning.
- Lower rolling resistance for enhanced fuel economy.
- Superior uniformity and high-speed integrity.

**CT95**

	RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER	TIRE WEIGHT (KG)	TIRE WEIGHT (LB)	MAX. INFLATION PRESSURE	OVERALL SECTION WIDTH (MEASURING RIM)	APPROVED RIM WIDTHS	TREAD DEPTH	REVS PER MILE
16	65	P205/65R16	94T	SL	BSW	15463310000	26.7	10.5	23.1	44	8.3 (6.0)	5.5 - 7.5	10/32	781	
	65	P215/65R17	98T	SL	BSW	15474690000	28.0	16.9	37.2	44	8.6 (6.5)	6.0 - 7.5	10/32	742	
	60	P215/60R17	95T	SL	BSW	15473890000	27.0	9.7	21.4	44	9.3 (6.5)	6.0 - 7.5	10/32	767	

**CH95**

14	60	P195/60R14	85H	SL	BSW	15447300000	23.2	7.5	16.5	44	7.9 (6.0)	5.5 - 7.0	10/32	878	
		175/65R15	84H	SL	BSW	03512130000	24.4	7.0	15.4	44	7.2 (5.0)	5.0 - 6.0	10/32	845	
		195/65R15	91H	SL	BSW	03512850000	25.0	8.5	18.6	44	8.2 (6.0)	5.5 - 7.0	10/32	828	
	15	65	205/65R15	94H	SL	BSW	03513080000	25.7	8.9	19.6	44	8.2 (6.0)	5.5 - 7.5	10/32	811
			P185/65R15	86H	SL	BSW	15447600000	24.5	8.2	18.0	51	7.4 (5.5)	5.0 - 6.5	10/32	849
			205/60R15	91H	SL	BSW	15461010000	24.7	9.0	19.8	44	8.2 (6.0)	5.5 - 7.5	10/32	836
		60	225/60R15	96H	SL	BSW	15469780000	25.6	10.8	23.7	44	9.0 (6.5)	6.0 - 8.0	10/32	814
			P195/60R15	87H	SL	BSW	15447800000	24.2	8.4	18.5	44	7.9 (6.0)	5.0 - 7.0	10/32	845
			P215/60R15	93H	SL	BSW	15447900000	25.2	9.6	21.1	60	8.7 (6.5)	6.0 - 7.5	10/32	827
			225/60R16	98H	SL	BSW	03514120000	26.6	10.8	23.8	44	9.0 (6.5)	6.0 - 8.0	10/32	784
16	60	235/60R16	100H	SL	BSW	15469800000	27.1	12.2	26.8	44	9.4 (7.0)	6.5 - 8.5	10/32	769	
		P215/60R16	94H	SL	BSW	15460540000	26.1	11.3	24.8	44	8.5 (6.5)	6.0 - 7.5	11/32	799	
		205/55R16	91H	SL	BSW	03513930000	24.9	8.8	19.4	44	8.4 (6.5)	5.5 - 7.5	10/32	831	
	55	205/55R16	91V	SL	BSW	03512330000	24.9	9.3	20.5	44	8.4 (6.5)	5.5 - 7.5	11/32	837	
		215/55R16	93H	SL	BSW	15469790000	25.3	10.1	22.2	44	8.9 (7.0)	6.0 - 7.5	10/32	824	
		225/55R16	95H	SL	BSW	03515740000	25.7	11.0	24.2	51	9.1 (7.0)	6.0 - 8.0	10/32	811	
		P205/55R16	89H	SL	BSW	15463340000	24.9	9.2	20.2	44	8.4 (6.5)	5.5 - 7.5	10/32	831	
		17	55	225/55R17	97H	SL	BSW	03514400000	27.1	10.8	23.7	44	9.3 (7.0)	6.0 - 8.0	10/32
235/55R17	99H			SL	BSW	03515370000	27.2	10.5	23.1	44	9.6 (7.5)	6.5 - 8.5	11/32	767	
P215/55R17	93H			SL	BSW	15473860000	26.3	10.2	22.3	44	8.9 (7.0)	6.0 - 7.5	10/32	792	
50	215/50R17		91H	SL	BSW	15470870000	25.5	10.0	22.0	44	8.9 (7.0)	6.0 - 7.5	10/32	818	
	215/45R17		87H	SL	BSW	15470880000	24.6	10.1	22.3	44	8.4 (7.0)	7.0 - 8.0	10/32	839	
45	225/45R17		91H	SL	BSW	03517330000	24.9	9.7	21.3	51	8.9 (7.5)	7.0 - 8.5	10/32	831	
	245/45R17		95H	SL	BSW	03515390000	25.7	10.8	23.8	44	9.6 (8.0)	7.5 - 9.0	10/32	811	
	205/40R17		80H	SL	BSW	15470860000	23.5	8.2	18.1	44	8.3 (7.5)	7.0 - 8.0	10/32	871	
18	60	P225/60R18	99H	SL	BSW	15474680000	28.0	13.4	29.5	51	9.0 (6.5)	6.0 - 8.0	10/32	734	
		P225/60R18	99H	SL	BSW	15474670000	28.6	13.8	30.4	44	8.9 (6.5)	6.0 - 8.0	10/32	734	
	50	235/50R18	97H	SL	BSW	03518470000	27.3	11.6	25.5	51	9.6 (8.0)	6.5 - 9.0	10/32	772	
	45	245/45R18	96H	SL	BSW	03515520000	27.0	11.2	24.7	51	10.0 (8.0)	7.5 - 9.0	10/32	772	
		255/45R18	99H	SL	BSW	03518280000	27.1	13.1	28.8	51	10.0 (8.5)	8.0 - 9.5	10/32	767	

**CV95**

15	65	195/65R15	91V	SL	BSW	03521530000	25.1	8.6	19.0	44	8.2 (6.0)	5.5 - 7.0	10/32	828
	60	195/60R15	88V	SL	BSW	03513440000	24.4	8.3	18.3	51	8.0 (6.0)	5.5 - 7.0	10/32	845
16	55	205/55R16	89V	SL	BSW	15471930000	24.9	9.2	20.3	44	8.4 (6.5)	5.5 - 7.5	10/32	831
		225/55R16	95V	SL	BSW	03517780000	25.6	10.1	22.3	51	9.4 (7.0)	6.0 - 8.0	10/32	810
		P225/55R16	94V	SL	BSW	15481600000	25.7	11.1	24.5	44	9.2 (7.0)	6.0 - 8.0	10/32	810
17	55	P225/55R17	95V	SL	BSW	15475480000	27.8	11.1	24.3	44	9.3 (7.0)	6.0 - 8.0	10/32	769
		205/50R17	93V	XL	BSW	03515940000	25.4	9.6	21.2	51	8.8 (6.5)	5.5 - 7.5	10/32	820
	50	225/50R17	94V	SL	BSW	03517770000	25.9	11.0	24.3	51	9.6 (7.0)	6.0 - 8.0	10/32	802
		P225/50R17	93V	SL	BSW	15476390000	25.9	10.5	23.1	44	9.2 (7.0)		10/32	803

**CONTITOURING CONTACT™ CT/CH/CV/CW95**

ULTRA HIGH PERFORMANCE

PERFORMANCE & TOURING

LIGHT TRUCK & SUV PERFORMANCE

LIGHT TRUCK & SUV LUXURY & COMFORT

VAN

WINTER



ULTRA HIGH PERFORMANCE

PERFORMANCE & TOURING

LIGHT TRUCK & SUV PERFORMANCE

LIGHT TRUCK & SUV LUXURY & COMFORT

VAN

WINTER

CONTI TOURING CONTACT™ CT/CH/CV/CW95

CW95

	RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER	TIRE WEIGHT (KG)	TIRE WEIGHT (LB)	MAX. INFLATION PRESSURE	OVERALL SECTION WIDTH (MEASURING RIM)	APPROVED RIM WIDTHS	TREAD DEPTH	REVS PER MILE
18	40	225/40R18	92W	XL	BSW	03522500000	25.1	10.5	23.1	51	9.3 (8.0)	7.5 - 9.0	10/32	827	
19	35	255/35R19	92W	SL	BSW	03520660000	25.9	11.3	24.9	51	10.4 (9.0)	8.5 - 10.0	10/32	801	

ORIGINAL EQUIPMENT APPLICATIONS - CT95

Nissan	16	65	P205/65R16	94T	SL	BSW	15463310000	26.7	10.5	23.1	44	8.3 (6.0)	5.5 - 7.5	10/32	781
Dodge/Chrysler	17	65	P215/65R17	98T	SL	BSW	15474690000	28.0	16.9	37.2	44	8.6 (6.5)	6.0 - 7.5	10/32	742
Ford		60	P215/60R17	95T	SL	BSW	15473890000	27.0	9.7	21.4	44	9.3 (6.5)	6.0 - 7.5	10/32	767

ORIGINAL EQUIPMENT APPLICATIONS - CH95

Mini	15	65	175/65R15	84H	SL	BSW	03512130000	24.4	7.0	15.4	44	7.2 (5.0)	5.0 - 6.0	10/32	845	
Volkswagen			195/65R15	91H	SL	BSW	03512850000	25.0	8.5	18.6	44	8.2 (6.0)	5.5 - 7.0	10/32	828	
Saab		205/65R15	94H	SL	BSW	03513080000	25.7	8.9	19.6	44	8.2 (6.0)	5.5 - 7.5	10/32	811		
Mercedes		60	205/60R15	91H	SL	BSW	15461010000	24.7	9.0	19.8	44	8.2 (6.0)	5.5 - 7.5	10/32	836	
Nissan			P195/60R15	87H	SL	BSW	15447800000	24.2	8.4	18.5	44	7.9 (6.0)	5.0 - 7.0	10/32	845	
Mercedes	16	60	225/60R16	98H	SL	BSW	03514120000	26.6	10.8	23.8	44	9.0 (6.5)	6.0 - 8.0	10/32	784	
BMW			205/55R16	91H	SL	BSW	03513950000	24.9	9.6	21.1	51	8.4 (6.5)	5.5 - 7.5	10/32	831	
Volkswagen		205/55R16	91H	SL	BSW	03513940000	24.9	8.5	18.7	44	8.4 (6.5)	5.5 - 7.5	10/32	831		
Jaguar		55	205/55R16	91H	SL	BSW	03512410000	24.9	8.8	19.4	44	8.4 (6.5)	5.5 - 7.5	10/32	831	
Volvo			205/55R16	91V	SL	BSW	03512330000	24.9	9.3	20.5	44	8.4 (6.5)	5.5 - 7.5	11/32	837	
Mercedes			225/55R16	95H	SL	BSW	03515740000	25.7	11.0	24.2	51	9.1 (7.0)	6.0 - 8.0	10/32	811	
Pontiac/Toyota			P205/55R16	89H	SL	BSW	15463340000	24.9	9.2	20.2	44	8.4 (6.5)	5.5 - 7.5	10/32	831	
Mercedes		50	225/50R16	92H	SL	BSW	03511480000	24.9	9.3	20.5	44	9.2 (7.0)	6.0 - 8.0	10/32	831	
Mercedes		17	55	225/55R17	97H	SL	BSW	03514400000	27.1	10.8	23.7	44	9.3 (7.0)	6.0 - 8.0	10/32	769
Audi				235/55R17	99H	SL	BSW	03515370000	27.2	10.5	23.1	44	9.6 (7.5)	6.5 - 8.5	11/32	767
Audi	45		225/45R17	91H	SL	BSW	03520330000	29.7	9.6	21.2	51	8.4 (7.5)	7.0 - 8.5	10/32	831	
Audi/Jaguar			225/45R17	91H	SL	BSW	03517330000	24.9	9.7	21.3	51	8.9 (7.5)	7.0 - 8.5	10/32	831	
Mercedes			245/45R17	95H	SL	BSW	03515390000	25.7	10.8	23.8	44	9.6 (8.0)	7.5 - 9.0	10/32	811	
Dodge/Chrysler	18	60	P225/60R18	99H	SL	BSW	15474680000	28.0	13.4	29.5	51	9.0 (6.5)	6.0 - 8.0	10/32	734	
Dodge/Chrysler			P225/60R18	99H	SL	BSW	15474670000	28.6	13.8	30.4	44	8.9 (6.5)	6.0 - 8.0	10/32	734	
Jaguar		50	235/50R18	97H	SL	BSW	03518470000	27.3	11.6	25.5	51	9.6 (8.0)	6.5 - 9.0	10/32	772	
Audi		45	255/45R18	99H	SL	BSW	03518280000	27.1	13.1	28.8	51	10.0 (8.5)	8.0 - 9.5	10/32	767	

**ORIGINAL EQUIPMENT APPLICATIONS - CV95**

	RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER	TIRE WEIGHT (KG)	TIRE WEIGHT (LB)	MAX. INFLATION PRESSURE	OVERALL SECTION WIDTH (MEASURING RIM)	APPROVED RIM WIDTHS	TREAD DEPTH	REVS PER MILE
Volvo	15	65	195/65R15	91V	SL	BSW	03521530000	25.1	8.6	19.0	44	8.2 (6.0)	5.5 - 7.0	10/32	828
Volvo		60	195/60R15	88V	SL	BSW	03513440000	24.4	8.3	18.3	51	8.0 (6.0)	5.5 - 7.0	10/32	845
Toyota	16	55	205/55R16	89V	SL	BSW	15471930000	24.9	9.2	20.3	44	8.4 (6.5)	5.5 - 7.5	10/32	831
BMW			225/55R16	95V	SL	BSW	03517780000	25.6	10.1	22.3	51	9.4 (7.0)	6.0 - 8.0	10/32	810
Ford			P225/55R16	94V	SL	BSW	15481600000	25.7	11.1	24.5	44	9.2 (7.0)	6.0 - 8.0	10/32	810
Nissan	17	55	P225/55R17	95V	SL	BSW	15475480000	27.8	11.1	24.3	44	9.3 (7.0)	6.0 - 8.0	10/32	769
BMW			205/50R17	93V	XL	BSW	03515940000	25.4	9.6	21.2	51	8.8 (6.5)	5.5 - 7.5	10/32	820
BMW			225/50R17	94V	SL	BSW	03517770000	25.9	11.0	24.3	51	9.6 (7.0)	6.0 - 8.0	10/32	802
Pontiac			P225/50R17	93V	SL	BSW	15476390000	25.9	10.5	23.1	44	9.2 (7.0)		10/32	803

**ORIGINAL EQUIPMENT APPLICATIONS - CW95**

Chrysler	18	40	225/40R18	92W	XL	BSW	03522500000	25.1	10.5	23.1	51	9.3 (8.0)	7.5 - 9.0	10/32	827
Chrysler	19	35	255/35R19	92W	SL	BSW	03520660000	25.9	11.3	24.9	51	10.4 (9.0)	8.5 - 10.0	10/32	801

**CONTITOURINGCONTACT™ CT/GH/CV/CW95**

ULTRA HIGH PERFORMANCE

PERFORMANCE & TOURING

LIGHT TRUCK & SUV PERFORMANCE

LIGHT TRUCK & SUV LUXURY & COMFORT

VAN

WINTER

# CONTIPREMIERCONTACT™

**SUPERIOR LUXURY AND COMFORT**  
THIS LUXURY TIRE FEATURES WIDE GROOVES  
THAT MAXIMIZE COMFORT AND MINIMIZE NOISE.



UTQG:	TREAD	TRACTION	TEMPERATURE
ALL SIZES	600	A	A

8	0	0	0	0	MILE LIMITED TREADWEAR WARRANTY
---	---	---	---	---	---------------------------------

130,000 KM

## FEATURES:

- Ultra-wide, four-groove tread pattern
- Acoustic Alterra Technology
- Tri-net Silica tread compound

## BENEFITS:

- Enhanced contact patch for luxurious ride. The four-groove tread channels water for impressive water dispersion.
- Creates a luxury tire with a tread pattern that minimizes noise and provides a comfortable ride.
- Provides long tread life with lower rolling resistance for improved fuel economy. Enhanced traction and braking in dry, rainy and winter driving conditions.

	RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER	TIRE WEIGHT (KG)	TIRE WEIGHT (LB)	MAX. INFLATION PRESSURE	OVERALL SECTION WIDTH (MEASURING RIM)	APPROVED RIM WIDTHS	TREAD DEPTH	REVS PER MILE
16	65	P215/65R16	96H	SL	BSW	15463660000	27.0	11.7	25.7	44	8.7 (6.5)	6.0 - 7.5	12/32	772	
		P205/60R16	91H	SL	BSW	15463670000	25.7	10.7	23.5	44	8.2 (6.0)	5.5 - 7.5	12/32	772	
		P215/60R16	94H	SL	BSW	15463530000	26.1	11.1	24.3	44	8.7 (6.5)	6.0 - 7.5	12/32	811	
	60	P225/60R16	97T	SL	WSW	15463570000	26.6	12.7	28.0	44	9.0 (6.5)	6.0 - 8.0	12/32	784	
		P225/60R16	97H	SL	BSW	15463560000	26.6	12.5	27.5	44	9.0 (6.5)	6.0 - 8.0	12/32	784	
		P235/60R16	99H	SL	BSW	15463580000	27.1	13.4	29.5	44	9.5 (7.0)	6.5 - 8.5	12/32	769	
		P205/55R16	89H	SL	BSW	15463590000	24.9	9.7	21.4	44	8.4 (6.5)	5.5 - 7.5	12/32	831	
		P215/55R16	91H	SL	BSW	15463600000	25.3	11.2	24.6	44	8.9 (7.0)	6.0 - 7.5	12/32	824	
	55	P225/55R16	94H	SL	BSW	15463610000	25.8	11.4	25.1	44	9.2 (7.0)	6.0 - 8.0	12/32	808	
17		55	P225/55R17	95H	SL	BSW	15463620000	26.8	12.5	27.5	44	9.2 (7.0)	6.0 - 8.0	12/32	778
	P235/55R17		98H	SL	BSW	15463630000	27.2	13.1	28.9	44	9.7 (7.5)	6.5 - 8.5	12/32	767	
	50	P215/50R17	90H	SL	BSW	15463640000	25.5	11.0	24.2	44	8.9 (7.0)	6.0 - 7.5	12/32	818	
	45	P215/45R17	87H	SL	BSW	15463650000	24.7	10.0	21.9	44	8.4 (7.0)	7.0 - 8.0	12/32	836	

**CONTI PREMIER CONTACT™**

ULTRA HIGH PERFORMANCE

PERFORMANCE & TOURING

LIGHT TRUCK & SUV PERFORMANCE

LIGHT TRUCK & SUV LUXURY & COMFORT

VAN

WINTER



# TOURING CONTACT™ AS

**OPTIMUM HANDLING FOR YOUR VEHICLE**  
THIS VERSATILE TIRE DELIVERS AN EXCEPTIONALLY QUIET  
AND COMFORTABLE RIDE WITH EXTENDED MILEAGE.



UTQG:	TREAD	TRACTION	TEMPERATURE
ALL SIZES	520	A	B

8	0	0	0	0	MILE LIMITED TREADWEAR WARRANTY
---	---	---	---	---	------------------------------------

130,000 KM

## FEATURES:

- Harmonized bead area and sidewall construction
- Wide circumferential grooves
- Multifunctional tread design

## BENEFITS:

- Enhanced ride and responsive handling.
- Exceptional quiet ride and extended mileage.
- Quickly evacuates water to reduce hydroplaning.

# TOURING CONTACT™ AS

	RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER	TIRE WEIGHT (KG)	TIRE WEIGHT (LB)	MAX. INFLATION PRESSURE	OVERALL SECTION WIDTH (MEASURING RIM)	APPROVED RIM WIDTHS	TREAD DEPTH	REVS PER MILE
13	70	P175/70R13	82S	SL	BSW	15462200000	22.7	6.7	14.7	44	7.0 (5.0)	4.5 - 6.0	10/32	892	
14	70	P175/70R14	84S	SL	BSW	15462260000	23.7	7.1	15.5	44	7.0 (5.0)	4.5 - 6.0	10/32	864	
		P185/70R14	87S	SL	PW	15462270000	24.3	7.6	16.7	44	7.4 (5.5)	4.5 - 6.0	10/32	848	
		P195/70R14	90S	SL	PW	15462280000	24.7	8.8	19.3	44	7.9 (6.0)	5.0 - 6.5	11/32	834	
		P205/70R14	93S	SL	PW	15462290000	25.4	9.2	20.2	44	8.2 (6.0)	5.0 - 7.0	11/32	821	
		P215/70R14	96S	SL	PW	15462300000	25.9	9.9	21.8	44	8.7 (6.5)	6.0 - 7.5	12/32	805	
	65	P175/65R14	81S	SL	BSW	15462310000	23.0	7.4	16.2	44	7.0 (5.0)	5.0 - 6.0	10/32	884	
		P185/65R14	85S	SL	BSW	15462320000	23.5	7.6	16.6	44	7.4 (5.5)	5.0 - 6.5	10/32	877	
		P195/65R14	88S	SL	BSW	15462330000	24.0	8.2	18.0	44	7.9 (6.0)	5.5 - 7.0	10/32	856	
		P185/60R14	82S	SL	BSW	15462340000	22.8	7.2	15.8	44	7.4 (5.5)	5.0 - 6.5	10/32	890	
P195/60R14	85S	SL	BSW	15462350000	23.2	7.7	16.9	44	7.9 (6.0)	5.5 - 7.0	10/32	878			
15	70	P205/70R15	95S	SL	PW	15462400000	26.3	10.1	22.2	44	8.2 (6.0)	5.0 - 7.0	11/32	793	
		P215/70R15	97S	SL	PW	15462410000	26.9	10.3	22.7	44	8.7 (6.5)	5.5 - 7.0	12/32	775	
		P225/70R15	100S	SL	PW	15462420000	27.4	10.8	23.8	44	9.0 (6.5)	6.0 - 7.5	12/32	761	
		P235/70R15	102S	SL	PW	15462430000	28.0	12.7	28.0	44	9.5 (7.0)	6.0 - 8.0	11/32	745	
	65	P195/65R15	89S	SL	BSW	15462450000	25.0	8.7	19.2	44	7.9 (6.0)	5.5 - 7.0	10/32	828	
		P205/65R15	92T	SL	BSW	15468240000	25.5	9.5	20.9	44	8.2 (6.0)	5.5 - 7.5	11/32	818	
		P205/65R15	92H	SL	BSW	15464320000	25.5	9.6	21.1	44	8.2 (6.0)	5.5 - 7.5	11/32	818	
		P215/65R15	95S	SL	BSW	15462470000	26.0	10.0	22.1	44	8.7 (6.5)	6.0 - 7.5	11/32	802	
		P195/60R15	87S	SL	BSW	15462480000	24.2	8.1	17.9	44	7.9 (6.0)	5.5 - 7.0	10/32	850	
P205/60R15	90S	SL	BSW	15462490000	24.7	8.9	19.7	44	8.2 (6.0)	5.5 - 7.5	11/32	836			
16	65	P215/65R16	96S	SL	BSW	15462510000	27.0	10.5	23.1	44	8.7 (6.5)	6.0 - 7.5	11/32	772	
	60	P215/60R16	94T	SL	BSW	15461760000	26.1	10.2	22.4	44	8.7 (6.5)	6.0 - 7.5	11/32	799	
		P225/60R16	97S	SL	BSW	15462530000	26.6	11.4	25.1	44	9.0 (6.5)	6.0 - 8.0	11/32	784	
	55	P205/55R16	89S	SL	BSW	15462540000	24.9	8.9	19.5	44	8.4 (6.5)	5.5 - 7.5	11/32	831	
17	60	P225/60R17	98S	SL	OWL	15476430000	27.6	11.9	26.2	44	9.0 (6.5)	6.0 - 8.0	10/32	755	
		P225/60R17	98S	SL	BSW	15476420000	27.6	10.7	23.5	44	9.0 (6.5)	6.0 - 8.0	10/32	755	
	50	P235/50R17	95S	SL	BSW	15471890000	26.3	12.3	27.1	44	9.7 (7.5)	6.5 - 8.5	10/32	793	

## ORIGINAL EQUIPMENT APPLICATIONS

Chevy	15	60	P195/60R15	87S	SL	BSW	15476400000	24.2	8.3	18.3	44	7.9 (6.0)	5.0 - 7.0	10/32	850
Toyota		65	P205/65R15	92T	SL	BSW	15468240000	25.5	9.5	20.9	44	8.2 (6.0)	5.5 - 7.5	11/32	818
Toyota			P205/65R15	92H	SL	BSW	15464320000	25.5	9.6	21.1	44	8.2 (6.0)	5.5 - 7.5	11/32	818
Ford	16	65	P215/65R16	96S	SL	BSW	15462510000	27.0	10.5	23.1	44	8.7 (6.5)	6.0 - 7.5	11/32	772
Nissan		60	P215/60R16	94T	SL	BSW	15476330000	26.2	10.2	22.4	44	8.7 (6.5)	6.0 - 7.5	11/32	797
Ford			P215/60R16	94T	SL	BSW	15461760000	26.1	10.2	22.4	44	8.7 (6.5)	6.0 - 7.5	11/32	799
Chevy/Buick/Pontiac	17	60	P225/60R17	98S	SL	OWL	15476430000	27.6	11.9	26.2	44	9.0 (6.5)	6.0 - 8.0	10/32	755
Chevy/Buick/Pontiac			P225/60R17	98S	SL	BSW	15476420000	27.6	10.7	23.5	44	9.0 (6.5)	6.0 - 8.0	10/32	755
GMC/Chevy		50	P235/50R17	95S	SL	BSW	15471890000	26.3	12.3	27.1	44	9.7 (7.5)	6.5 - 8.5	10/32	793

ULTRA HIGH PERFORMANCE

PERFORMANCE & TOURING

LIGHT TRUCK & SUV PERFORMANCE

LIGHT TRUCK & SUV LUXURY & COMFORT

VAN

WINTER

# CONTICROSSCONTACT™ UHP

THE ULTIMATE IN STYLE AND PERFORMANCE  
THIS TIRE DELIVERS STABILITY, CONTROL AND  
RESPONSIVENESS AT THE HIGHEST LEVEL.



UTQG:	TREAD	TRACTION	TEMPERATURE
ALL SIZES	420	AA	A

## FEATURES:

- Asymmetric tread with wide circumferential grooves
- Bionic contour
- Advanced silica technology
- Rim flange rib protector

## BENEFITS:

- Enhanced grip for braking and driving pleasure. Low noise. Reduced risk of hydroplaning.
- Reduced braking distances. Improved cornering stability.
- Outstanding dry and wet grip and low rolling resistance.
- Protects expensive rims from curb damage.



	RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER	TIRE WEIGHT (KG)	TIRE WEIGHT (LB)	MAX. INFLATION PRESSURE	OVERALL SECTION WIDTH (MEASURING RIM)	APPROVED RIM WIDTHS	TREAD DEPTH	REVS PER MILE
16	60	235/60R16	100H	SL	BSW	03520680000	27.1	10.0	22.0	51	9.6 (7.5)	6.5 - 8.5	10/32	765	
17	55	225/55R17	97W	SL	BSW	03520670000	26.9	10.8	23.7	51	9.2 (7.0)	6.0 - 8.0	10/32	774	
18	55	255/55R18	109V	XL	BSW	03546920000	29.0	14.0	30.8	51	10.4 (8.0)	7.0 - 9.0	10/32	715	
	50	285/50R18	109W	SL	BSW	03520700000	29.3	15.0	33.0	51	11.7 (9.0)	8.0 - 10.0	10/32	708	
19	50	255/50R19	107V	XL	BSW	03546380000	29.1	15.2	33.4	51	10.4 (8.0)	7.0 - 9.0	10/32	712	
20	55	275/55ZR20	117W	XL	BSW	03545700000	31.9	14.5	31.9	51	11.2 (8.5)	7.0 - 9.5	11/32	653	
		255/50ZR20	109W	XL	BSW	03520690000	30.2	15.6	34.4	51	10.3 (8.0)	7.0 - 9.0	10/32	689	
	50	285/50ZR20	116W	XL	BSW	03545710000	31.2	14.5	31.9	51	11.7 (9.0)	8.0 - 10.0	11/32	668	
		275/45ZR20	110W	XL	BSW	03545720000	29.7	14.5	31.9	51	10.7 (9.0)	8.5 - 10.0	10/32	701	
	45	295/45ZR20	114W	XL	BSW	03545600000	30.5	14.9	32.7	51	11.7 (10.0)	9.5 - 11.0	10/32	682	
		275/40R20	106Y	XL	BSW	03545590000	28.7	16.0	35.2	51	10.8 (9.5)	9.0 - 11.0	10/32	728	
40	295/40R20	106Y	XL	BSW	03545620000	29.3	14.9	32.7	51	11.9 (10.5)	10.0 - 11.5	10/32	709		
22	45	305/45ZR22	118W	XL	BSW	03545810000	32.8	20.0	44.0	51	12.0 (10.0)	9.5 - 11.5	10/32	636	
	40	305/40ZR22	114W	XL	BSW	03520710000	31.6	20.0	43.9	51	12.3 (11.0)	10.0 - 12.0	10/32	657	
	35	265/35R22	102Y	XL	BSW	03545630000	29.3	13.5	29.7	51	10.7 (9.5)	9.0 - 10.5	10/32	709	
	30	295/30R22	103Y	XL	BSW	03545640000	29.0	14.6	32.1	51	11.9 (10.5)	10.0 - 11.0	10/32	715	
		315/30R22	107W	XL	BSW	03545770000	29.4	15.5	34.1	51	12.4 (11.0)	10.5 - 11.5	10/32	708	
23	40	305/40ZR23	115W	XL	BSW	03547030000	32.6	22.0	48.4	51	12.3 (11.0)	10.0 - 12.0	11/32	639	
	25	315/25R23	102Y	XL	BSW	03545650000	29.2	17.0	37.4	51	12.8 (11.5)	11.0 - 12.0	10/32	711	
24	35	315/35ZR24	114W	XL	BSW	03547040000	32.7	21.0	46.2	51	12.4 (11.0)	10.5 - 12.5	10/32	638	

### ORIGINAL EQUIPMENT APPLICATIONS

Mercedes	18	55	255/55R18	105W	SL	BSW	03546950000	29.0	16	35.2	51	10.4 (8.0)	7.0 - 9.0	11/32	718
Land Rover			255/55R18	109V	XL	BSW	03546920000	29.0	14	30.8	51	10.4 (8.0)	7.0 - 9.0	10/32	715
Land Rover	19	50	255/50R19	107V	XL	BSW	03546380000	29.1	15.2	33.4	51	10.4 (8.0)	7.0 - 9.0	10/32	712

NEW PRODUCT AVAILABLE SPRING 2005

CONTIGROSSCONTACT™ UHP

ULTRA HIGH PERFORMANCE

PERFORMANCE & TOURING

LIGHT TRUCK & SUV PERFORMANCE

LIGHT TRUCK & SUV LUXURY & COMFORT

VAN

WINTER



# CONTI 4x4 SPORTCONTACT™

**THE DEFINITION OF RESPONSIVENESS**  
EXCELLENT HIGH CORNERING AND HIGH-SPEED CONTROL ARE BENEFITS OF THIS TIRE THAT SERVES AS ORIGINAL EQUIPMENT ON THE WORLD'S FOREMOST VEHICLES.



UTQG:	TREAD	TRACTION	TEMPERATURE
ALL SIZES	280	A	A

## FEATURES:

- Asymmetrical tread design with compact outer shoulder blocks
- Continuous center tread ribs
- Wide longitudinal and lateral water evacuation grooves
- Optimized off-set tread blocks and grooves
- Rim flange rib protector

## BENEFITS:

- Enhanced cornering stability and control.
- Precise steering response and high speed stability.
- Maximum hydroplaning resistance.
- For a smooth, quiet ride.
- Protects the rim from curb damage.

	RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER	TIRE WEIGHT	TIRE WEIGHT (KG)	MAX. INFLATION PRESSURE	OVERALL SECTION WIDTH (MEASURING RIM)	APPROVED RIM WIDTHS	TREAD DEPTH	REVS PER MILE
18	55	255/55R18	109Y	XL	BSW	03546250000	26.8	16.0	35.1	51	9.2 (7.0)	6.0 - 8.0	11/32	778	
19	50	255/50R19	103W	SL	BSW	03546270000	29.3	14.3	31.4	51	10.3 (8.0)	7.0 - 9.0	11/32	712	
	45	275/45R19	108Y	XL	BSW	03546310000	28.8	16.1	35.3	51	10.7 (9.0)	8.5 - 10.5	10/32	724	
		285/45R19	107W	SL	BSW	03546280000	29.1	14.9	32.9	51	11.7 (9.0)	8.0 - 10.0	10/32	717	
20	40	275/40R20	106Y	XL	BSW	03546370000	28.7	16.0	35.2	51	10.9 (9.5)	9.0 - 10.5	10/32	726	
	35	315/35ZR20	Z	XL	BSW	03546300000	28.7	15.0	33.0	51	12.6 (11.0)	10.5 - 12.5	10/32	726	

### ORIGINAL EQUIPMENT APPLICATIONS

Porsche	18	55	255/55R18	109Y	XL	BSW	03546250000	26.8	16.0	35.1	51	9.2 (7.0)	6.0 - 8.0	11/32	778
Porsche	19	45	275/45R19	108Y	XL	BSW	03546310000	28.8	16.1	35.3	51	10.7 (9.0)	8.5 - 10.5	10/32	724
Porsche	20	40	275/40R20	106Y	XL	BSW	03546370000	28.7	16.0	35.2	51	10.9 (9.5)	9.0 - 10.5	10/32	726

# CONTI 4x4 SPORTCONTACT™

ULTRA HIGH PERFORMANCE

PERFORMANCE & TOURING

LIGHT TRUCK & SUV PERFORMANCE

LIGHT TRUCK & SUV LUXURY & COMFORT

VAN

WINTER

# CONTICROSSCONTACT™ LX

## SMOOTH AND COMFORTABLE

THIS LUXURY TIRE MINIMIZES NOISE AND PROVIDES A CONSISTENT RIDE IN ALL-SEASON CONDITIONS.



NEW PRODUCT FOR 2005

UTQG:	TREAD	TRACTION	TEMPERATURE
ALL SIZES	680	A	B

6	5	0	0	0	MILE LIMITED TREADWEAR WARRANTY
---	---	---	---	---	---------------------------------

100,000 KM

### FEATURES:

- Asymmetric tread pattern
- Tri-net silica tread compound
- Spiral-wound, jointless cap plies
- Acoustic Alterra Technology
- New progressive interlocking sipes

### BENEFITS:

- Optimized performance of the contact patch for a predictable luxury ride.
- Provides improved traction in dry, rainy, and winter driving conditions. Long tread life with lower rolling resistance for increased fuel economy.
- Excellent ride and driving comfort.
- Minimizes noise and provides a comfortable ride.
- Interlocks the tread blocks to provide excellent traction and directional control in all-season conditions.



	RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER	TIRE WEIGHT (KG)	TIRE WEIGHT (LB)	MAX. INFLATION PRESSURE	OVERALL SECTION WIDTH (MEASURING RIM)	APPROVED RIM WIDTHS	TREAD DEPTH	REVS PER MILE
15	75	235/75R15	109T	XL OWL	15475530000	28.9	15.7	34.5	44	9.3 (6.5)	6.0 - 8.0	12/32	727		
	70	265/70R15	112H	SL BSW	15475540000	29.6	15.0	33.0	51	10.7 (8.0)	7.0 - 9.0	12/32	710		
16	75	225/75R16	104T	SL BSW	15480120000	29.3	16.5	36.2	44	8.8 (6.0)	6.0 - 7.5	12/32	718		
		265/75R16	116T	SL OWL	15480190000	31.6	17.2	37.9	44	10.5 (7.5)	7.0 - 9.0	12/32	659		
	70	225/70R16	102H	SL BSW	15475550000	28.4	15.8	34.7	44	9.0 (6.5)	6.0 - 7.5	12/32	734		
		225/70R16	102T	SL BSW	15480130000	28.4	12.5	27.6	44	9.0 (6.5)	6.0 - 7.5	12/32	740		
		235/70R16	106T	SL OWL	15475570000	29.0	15.5	34.1	44	9.4 (7.0)	6.0 - 8.0	12/32	725		
		235/70R16	106H	SL BSW	03545670000	29.0	17.5	38.5	51	9.5 (7.0)	6.0 - 8.0	12/32	720		
		245/70R16	107T	SL OWL	15475580000	29.5	15.5	34.1	44	9.8 (7.0)	6.0 - 8.0	12/32	713		
		245/70R16	107H	SL BSW	03545660000	29.5	15.2	33.4	51	9.8 (7.0)	6.0 - 8.0	12/32	707		
		265/70R16	112H	SL BSW	15475610000	30.6	18.1	39.8	44	10.7 (8.0)	7.0 - 9.0	12/32	687		
		275/70R16	114T	SL BSW	15480160000	31.2	18.7	41.2	44	11.0 (8.0)	7.0 - 9.0	12/32	673		
65	255/65R16	109H	SL BSW	15475600000	29.1	15.5	34.1	44	10.2 (7.5)	7.0 - 9.0	12/32	722			
17	70	265/70R17	115T	SL BSW	15480170000	31.7	18.2	40.1	44	10.7 (8.0)	7.0 - 9.0	12/32	663		
	65	235/65R17	108H	XL BSW	15475630000	29.1	15.0	33.0	51	9.4 (7.0)	6.5 - 8.5	12/32	722		
	60	255/60R17	106H	SL BSW	15475640000	29.1	16.1	35.4	51	10.2 (7.5)	7.0 - 9.0	12/32	722		
		275/60R17	110T	SL OWL	15475660000	30.0	17.6	38.6	44	11.0 (8.0)	7.5 - 9.5	12/32	701		
18	60	285/60R18	116T	SL BSW	15480180000	31.5	20.5	45.2	44	11.5 (8.5)	8.0 - 10.0	12/32	667		
	55	255/55R18	109H	XL BSW	15475670000	29.0	15.9	35.0	51	10.4 (8.0)	7.0 - 9.0	12/32	718		

NEW PRODUCT AVAILABLE SPRING 2005

CONTIGROSSCONTACT™ LX

ULTRA HIGH PERFORMANCE

PERFORMANCE & TOURING

LIGHT TRUCK & SUV PERFORMANCE

LIGHT TRUCK & SUV LUXURY & COMFORT

VAN

WINTER



# CONTI 4x4 CONTACT™

**ALL-SEASON PERFORMANCE AND PURPOSE**  
ENHANCED GRIP BOTH ON AND OFF-ROAD PROVIDE A QUIET  
AND COMFORTABLE RIDE IN ALL-SEASON CONDITIONS.



UTQG:	TREAD	TRACTION	TEMPERATURE
ALL SIZES	360	A	A

## FEATURES:

- Proven OE Fitments
- Three circumferential ribs
- Wide circumferential and lateral drainage grooves
- Multiple tread sipes
- Digitally-designed off-set tread blocks and curved grooves

## BENEFITS:

- Selected tire by many of the finest European automobile manufacturers.
- Directional stability and fast precise steering response.
- Fast water evacuation for maximum hydroplaning resistance.
- Enhanced grip on and off-road.
- For a smooth, quiet, and comfortable ride.

	RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER	TIRE WEIGHT (KG)	TIRE WEIGHT (LB)	MAX. INFLATION PRESSURE	OVERALL SECTION WIDTH (MEASURING RIM)	APPROVED RIM WIDTHS	TREAD DEPTH	REVS PER MILE
15	80	195/80R15	96H	SL	BSW	03546600000	27.3	10.5	23.1	44	8.0 (5.5)	5.5 - 6.5	10/32	764	
	70	205/70R15	96T	SL	BSW	03546170000	26.3	9.7	21.3	51	8.2 (6.0)	5.0 - 7.0	11/32	793	
	65	185/65R15	88T	SL	BSW	03542620000	24.5	7.6	16.8	44	7.4 (5.5)	5.0 - 6.5	11/32	849	
16	70	225/70R16	102H	SL	BSW	03546090000	28.4	13.5	29.7	51	9.0 (6.5)	6.0 - 7.5	11/32	734	
	65	255/65R16	109H	SL	BSW	03546200000	29.1	14.5	31.8	36	10.2 (7.5)	7.0 - 9.0	11/32	716	
17	70	235/70R17	111H	XL	BSW	03545170000	30.0	11.0	24.2	51	9.5 (7.0)	6.0 - 8.0	11/32	695	
	65	235/65R17	104V	SL	BSW	15480050000	29.0	14.6	32.1	51	9.5 (7.0)	6.5 - 8.5	11/32	719	
		235/65R17	104H	SL	BSW	15480040000	29.1	14.6	32.1	51	9.5 (7.0)	6.0 - 8.5	11/32	718	
	60	255/60R17	106H	SL	BSW	15449190000	29.1	15.4	33.9	44	10.2 (6.5)	6.0 - 8.0	10/32	716	
	55	275/55R17	109V	SL	BSW	15449180000	28.9	16.3	35.8	44	11.2 (8.5)	7.5 - 9.5	10/32	721	
18	60	P225/60R18	99H	SL	BSW	15474570000	28.6	11.4	25.1	51	9.0 (6.5)	6.0 - 8.0	10/32	728	
	55	255/55R18	105H	SL	BSW	15480060000	29.0	14.2	31.2	51	10.4 (8.0)	7.0 - 9.0	10/32	718	
	50	235/50R18	101H	XL	BSW	03545250000	27.3	11.1	24.4	51	9.7 (7.5)	6.5 - 8.5	11/32	765	

### ORIGINAL EQUIPMENT APPLICATIONS

Volvo	16	70	225/70R16	102H	SL	BSW	03546090000	28.4	13.5	29.7	51	9.0 (6.5)	6.0 - 7.5	11/32	734
Land Rover	17	70	235/70R17	111H	XL	BSW	03545170000	30.0	11.0	24.2	51	9.5 (7.0)	6.0 - 8.0	11/32	695
Mercedes		65	235/65R17	104V	SL	BSW	15480050000	29.0	14.6	32.1	51	9.5 (7.0)	6.5 - 8.5	11/32	719
Mercedes		65	235/65R17	104H	SL	BSW	15480040000	29.1	14.6	32.1	51	9.5 (7.0)	6.0 - 8.5	11/32	718
Mercedes		60	255/60R17	106H	SL	BSW	15449190000	29.1	15.4	33.9	44	10.2 (6.5)	6.0 - 8.0	10/32	716
Mercedes		55	275/55R17	109V	SL	BSW	15449180000	28.9	16.3	35.8	44	11.2 (8.5)	7.5 - 9.5	10/32	721
Dodge/Chrysler	18	60	P225/60R18	99H	SL	BSW	15474570000	28.6	11.4	25.1	51	9.0 (6.5)	6.0 - 8.0	10/32	728
Mercedes		55	255/55R18	105H	SL	BSW	15480060000	29.0	14.2	31.2	51	10.4 (8.0)	7.0 - 9.0	10/32	718
Land Rover		50	235/50R18	101H	XL	BSW	03545250000	27.3	11.1	24.4	51	9.7 (7.5)	6.5 - 8.5	11/32	765

CONTI 4x4 CONTACT™

ULTRA HIGH PERFORMANCE

PERFORMANCE & TOURING

LIGHT TRUCK & SUV PERFORMANCE

LIGHT TRUCK & SUV LUXURY & COMFORT

VAN

WINTER

# CONTITRAC™ SUV

A VERSATILE BLEND OF SAFETY AND COMFORT  
 EXCELLENT TRACTION ALLOWS FOR ALL-SEASON  
 PERFORMANCE AND SOME OFF-ROAD USE.



UTQG:	TREAD	TRACTION	TEMPERATURE
ALL SIZES	520	A	B

6	0	0	0	0	MILE LIMITED TREADWEAR WARRANTY
---	---	---	---	---	---------------------------------

96,000 KM

## FEATURES:

- Solid center rib
- Wide, deep tread grooves
- Optimized tread pitch sequencing
- Staggered tread blocks

## BENEFITS:

- Provides smooth, stable handling and increased tread life.
- Enhanced resistance to hydroplaning for comfort and safety.
- Exceptional quiet ride and comfort.
- Provides biting traction for excellent all-season performance and light off-road use.

# CONTITRAC™ SUV

	RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER	TIRE WEIGHT (KG)	TIRE WEIGHT (LB)	MAX. INFLATION PRESSURE	OVERALL SECTION WIDTH (MEASURING RIM)	APPROVED RIM WIDTHS	TREAD DEPTH	REVS PER MILE
15	75	LT235/75R15	104/101Q	C	OWL	04570120000	28.9	13.9	30.6	50	9.3 (6.5)	6.0 - 7.0	14/32	721	
		P205/75R15	97S	SL	OWL	15465940000	27.1	10.6	23.2	44	8.0 (5.5)	5.0 - 7.0	13/32	769	
		P215/75R15	100S	SL	OWL	15465880000	27.7	12.4	27.2	44	8.5 (6.0)	5.5 - 7.0	13/32	753	
		P225/75R15	102S	SL	OWL	15465870000	28.3	13.0	28.7	44	8.8 (6.0)	6.0 - 7.5	13/32	737	
		P235/75R15	108S	XL	OWL	15465860000	28.9	14.2	31.2	51	9.3 (6.5)	6.0 - 8.0	13/32	721	
		P235/75R15	105S	SL	OWL	15465850000	28.9	13.8	30.4	44	9.3 (6.5)	6.0 - 8.0	13/32	721	
	70	P265/75R15	112S	SL	OWL	15465930000	30.7	16.2	35.7	44	10.5 (7.5)	7.0 - 9.0	13/32	679	
		P225/70R15	100S	SL	OWL	15465890000	27.4	12.3	27.1	44	9.0 (6.5)	6.0 - 7.5	13/32	761	
		P235/70R15	102S	SL	OWL	15466050000	28.0	13.2	29.1	44	9.4 (7.0)	6.0 - 8.0	13/32	745	
		P255/70R15	108S	SL	OWL	15466750000	29.1	14.6	32.0	44	10.2 (7.5)	6.5 - 8.5	13/32	716	
		P265/70R15	110S	SL	OWL	15466760000	29.6	15.3	33.6	44	10.7 (8.0)	7.0 - 9.0	13/32	704	
		31X10.50R15LT	109Q	C	OWL	04570110000	30.5	16.5	36.3	50	10.6 (8.5)	7.0 - 9.0	16/32	684	
16	85	LT235/85R16	120/116Q	E	OWL	04570140000	31.7	19.5	42.9	80	9.3 (6.5)	6.0 - 7.5	14/32	658	
	75	LT225/75R16	110/107Q	D	OWL	04570130000	29.3	16.3	35.9	65	8.8 (6.0)	6.0 - 7.0	14/32	712	
		P225/75R16	104S	SL	OWL	15466010000	29.3	13.4	29.4	44	8.8 (6.0)	6.0 - 7.5	13/32	712	
		P235/75R16	106S	SL	OWL	15466030000	29.8	14.5	31.8	44	9.3 (6.5)	6.0 - 8.0	11/32	700	
		P245/75R16	109S	SL	OWL	15466040000	30.5	15.7	34.5	44	9.8 (7.0)	6.5 - 8.0	11/32	684	
	70	P215/70R16	99S	SL	OWL	15466060000	27.9	12.1	26.7	44	8.7 (6.5)	5.5 - 7.0	13/32	747	
		P225/70R16	101S	SL	OWL	15465920000	28.4	12.8	28.1	44	9.0 (6.5)	6.0 - 7.5	13/32	734	
		P245/70R16	106S	SL	OWL	15465910000	29.5	14.8	32.6	44	9.8 (7.0)	6.0 - 8.0	13/32	707	
		P255/70R16	109S	SL	OWL	15466020000	30.1	15.6	34.2	44	10.2 (7.5)	6.5 - 8.5	11/32	693	
		P265/70R16	111S	SL	OWL	15466000000	30.6	16.4	36.1	44	10.7 (8.0)	7.0 - 9.0	13/32	681	
P275/70R16		114S	SL	OWL	15465950000	31.2	17.1	37.5	44	11.0 (8.0)	7.0 - 9.0	13/32	668		
17	70	P265/70R17	113S	SL	OWL	15464770000	31.6	17.0	37.3	44	10.9 (8.0)	7.0 - 9.0	12/32	660	
		P265/70R17	113S	SL	BSW	15464760000	31.6	16.6	36.5	44	10.9 (8.0)	7.0 - 9.0	12/32	660	
	60	P275/60R17	110S	SL	OWL	15466070000	30.0	17.4	38.2	44	11.0 (8.0)	7.5 - 9.5	13/32	695	

## ORIGINAL EQUIPMENT APPLICATIONS

Ford	17	70	P265/70R17	113S	SL	OWL	15464770000	31.6	17.0	37.3	44	10.9 (8.0)	7.0 - 9.0	12/32	660
Ford			P265/70R17	113S	SL	BSW	15464760000	31.6	16.6	36.5	44	10.9 (8.0)	7.0 - 9.0	12/32	660

ULTRA HIGH PERFORMANCE

PERFORMANCE & TOURING

LIGHT TRUCK & SUV PERFORMANCE

LIGHT TRUCK & SUV LUXURY & COMFORT

VAN

WINTER



**EXCELLENT ALL-SEASON PERFORMANCE, RIDE AND COMFORT**  
WIDE, DEEP TREAD GROOVES AND A SOLID CENTER RIB PROVIDE SMOOTH,  
STABLE HANDLING AND INCREASED TREAD LIFE.



UTQG:	TREAD	TRACTION	TEMPERATURE
P225/70R15	420	A	A
ALL OTHER SIZES	520	A	B

## FEATURES:

- Solid center rib
- Wide, deep tread grooves
- Optimized tread pitch sequencing
- Staggered tread blocks

## BENEFITS:

- Provides smooth, stable handling and increased tread life.
- Enhanced resistance to hydroplaning for comfort and safety.
- Exceptional quiet ride and comfort.
- Provides biting traction for excellent all-season performance and light off-road use.

	RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER	TIRE WEIGHT (KG)	TIRE WEIGHT (LB)	MAX. INFLATION PRESSURE	OVERALL SECTION WIDTH (MEASURING RIM)	APPROVED RIM WIDTHS	TREAD DEPTH	REVS PER MILE
15	70	P225/70R15	100S	SL	OWL	15473450000	27.4	11.9	26.2	44	9.0 (6.5)	6.0 - 7.5	12/32	767	
		P225/70R15	100S	SL	BSW	15473440000	27.4	11.6	25.5	44	9.0 (6.5)	6.0 - 7.5	12/32	767	
16	70	P235/70R16	104T	SL	OWL	15481000000	29.0	14.4	31.7	44	9.4 (7.0)	6.0 - 8.0	13/32	720	
		P235/70R16	104T	SL	OWL	15476690000	29.0	14.4	31.7	44	9.4 (7.0)	6.0 - 8.0	13/32	720	
		P235/70R16	104T	SL	BSW	15476680000	29.0	14.1	31.0	44	9.4 (7.0)	6.0 - 8.0	13/32	720	
17	75	LT245/75R17	121/118S	SL	OWL	04567500000	31.5	21.6	47.4	80	9.7 (7.0)	6.0 - 7.5	11/32	662	
		LT245/75R17	121/118S	E	BSW	04567490000	31.5	21.6	47.5	80	9.7 (7.0)	6.0 - 7.5	11/32	662	
	65	P255/65R17	108S	SL	OWL	15463460000	30.1	15.7	34.5	44	10.2 (7.5)	7.0 - 9.0	12/32	696	
18	70	LT275/70R18	125/122S	E	BSW	04567510000	33.2	23.9	52.5	80	10.9 (8.0)	7.0 - 8.5	12/32	628	
		P265/70R18	114S	SL	BSW	15482600000	32.6	19.0	41.7	44	10.7 (8.0)	7.0 - 9.0	11/32	639	
	65	LT275/65R18	123/120S	E	OWL	04567540000	33.4	24.6	54.1	80	10.9 (8.0)	7.0 - 8.5	15/32	629	
		LT275/65R18	123/120S	E	BSW	04567530000	33.2	24.3	53.4	80	10.9 (8.0)	7.0 - 8.5	12/32	628	

### ORIGINAL EQUIPMENT APPLICATIONS

Ford	15	70	P225/70R15	100S	SL	OWL	15473450000	27.4	11.9	26.2	44	9.0 (6.5)	6.0 - 7.5	12/32	767
Ford			P225/70R15	100S	SL	BSW	15473440000	27.4	11.6	25.5	44	9.0 (6.5)	6.0 - 7.5	12/32	767
Ford	16	70	P235/70R16	104T	SL	OWL	15476690000	29.0	14.4	31.7	44	9.4 (7.0)	6.0 - 8.0	13/32	720
Ford			P235/70R16	104T	SL	BSW	15476680000	29.0	14.1	31.0	44	9.4 (7.0)	6.0 - 8.0	13/32	720
Ford	17	75	LT245/75R17	121/118S	E	OWL	04567500000	31.5	21.6	47.4	80	9.7 (7.0)	6.0 - 7.5	11/32	662
Ford			LT245/75R17	121/118S	E	BSW	04567490000	31.5	21.6	47.5	80	9.7 (7.0)	6.0 - 7.5	11/32	662
Ford		65	P255/65R17	108S	SL	OWL	15463460000	30.1	15.7	34.5	44	10.2 (7.5)	7.0 - 9.0	12/32	696
Ford	18	70	LT275/70R18	125/122S	E	BSW	04567510000	33.2	23.9	52.5	80	10.9 (8.0)	7.0 - 8.5	12/32	628
Nissan			P265/70R18	114S	SL	BSW	15482600000	32.6	19.0	41.7	44	10.7 (8.0)	7.0 - 9.0	11/32	639
Ford		65	LT275/65R18	123/120S	E	OWL	04567540000	33.4	24.6	54.1	80	10.9 (8.0)	7.0 - 8.5	15/32	629
Ford			LT275/65R18	123/120S	E	BSW	04567530000	33.2	24.3	53.4	80	10.9 (8.0)	7.0 - 8.5	12/32	628

CONTITRAC™

ULTRA HIGH PERFORMANCE

PERFORMANCE & TOURING

LIGHT TRUCK & SUV PERFORMANCE

LIGHT TRUCK & SUV LUXURY & COMFORT

VAN

WINTER

# CONTI TRAC™ TR/AW/AT

**TR - EXCELLENT OFF-ROAD PERFORMANCE AND HIGHWAY COMFORT**  
 GERMAN ENGINEERED TO DELIVER PRECISE STEERING, ENHANCED STABILITY AND TRACTION FOR BOTH ON AND OFF-ROAD USE.

**AW - ON AND OFF-ROAD STABILITY AND CONTROL**  
 A STAGGERED TREAD PATTERN AND DEEP GROOVES GIVE THIS TIRE EXCELLENT TRACTION IN A VARIETY OF CONDITIONS.

**AT - VERSATILITY ON-ROAD AND OFF**  
 SUPERIOR STEERING RESPONSE AND LOW TIRE NOISE MAKE FOR A COMFORTABLE RIDE IN A NUMBER OF DIFFERENT CONDITIONS.



**UTQG: TREAD TRACTION TEMP**  
 ALL SIZES 520 A B

**UTQG: TREAD TRACTION TEMP**  
 ALL SIZES 420 B B

**UTQG: TREAD TRACTION TEMP**  
 ALL SIZES 400 B B

**FEATURES:**

- Continuous central ribs, fine venting and lateral grooves
- Four wide circumferential tread grooves
- Staggered tread pattern and deep self-cleaning grooves

**BENEFITS:**

- Precise steering response and low tire noise for a comfortable ride.
- Provides enhanced stability and control on wet roads.
- Provides excellent snow and mud traction for on and off-road use.

**FEATURES:**

- Sequentially optimized tread pattern
- Solid Center Rib
- Wide circumferential tread grooves

**BENEFITS:**

- Quiet all-season performance.
- Provides smooth, stable handling and increased tread life.
- Provides resistance to hydroplaning for comfort and safety.

**FEATURES:**

- Wide flat tread arc
- Wide circumferential tread grooves
- "M" and "S" rated

**BENEFITS:**

- Superior wet and dry traction.
- Exceptional quiet ride and extended mileage.
- All-season performance.

ORIGINAL EQUIPMENT APPLICATIONS - CONTITRAC™ TR

	RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER	TIRE WEIGHT (KG)	TIRE WEIGHT (LB)	MAX. INFLATION PRESSURE	OVERALL SECTION WIDTH (MEASURING RIM)	APPROVED RIM WIDTHS	TREAD DEPTH	REVS PER MILE
Ford	17	70	P265/70R17	113H	SL	BSW	15476130000	31.8	18.7	41.2	44	10.7 (8.0)	7.0 - 9.0	14/32	663
Ford			P265/70R17	113S	SL	OWL	15464780000	31.8	17.9	39.4	44	11.1 (8.0)	7.0 - 9.0	14/32	656
Chevrolet/GMC		65	P245/65R17	105S	SL	OWL	15463550000	29.5	15.6	34.3	44	9.8 (7.0)	7.0 - 8.5	13/32	706
Chevrolet/GMC			P245/65R17	105S	SL	BSW	15463540000	29.5	15.5	34.1	44	9.8 (7.0)	7.0 - 8.5	13/32	706
Ford	18	70	LT275/70R18	125/122S	E	OWL	04567560000	32.1	27.4	60.2	80	10.9 (8.0)	7.0 - 9.0	12/32	653
Ford			LT275/70R18	125/122S	E	BSW	04567550000	32.1	27.4	60.2	80	10.9 (8.0)	7.0 - 9.0	12/32	653

ORIGINAL EQUIPMENT APPLICATIONS - CONTITRAC™ AW

Lincoln	17	60	P275/60R17	110S	SL	OWL	15461820000	30.0	16.9	37.3	44	11.0 (8.0)	7.5 - 9.5	11/32	701
---------	----	----	------------	------	----	-----	-------------	------	------	------	----	------------	-----------	-------	-----

ORIGINAL EQUIPMENT APPLICATIONS - CONTITRAC™ AT

Lincoln	17	75	P255/75R17	113S	SL	OWL	15427880000	32.1	17.4	38.3	44	10.0 (7.0)	6.5 - 8.5	14/32	655
---------	----	----	------------	------	----	-----	-------------	------	------	------	----	------------	-----------	-------	-----

CONTITRAC™ TR / AW / AT

ULTRA HIGH PERFORMANCE

PERFORMANCE & TOURING

LIGHT TRUCK & SUV PERFORMANCE

LIGHT TRUCK & SUV LUXURY & COMFORT

VAN

WINTER



# VANCO™ 8 / VANCOCONTACT™ / VANCO™ 4 SEASON

**VANCO 8 – OPTIMIZED FUEL ECONOMY AND EXTENDED TREAD LIFE**  
THE TECHNOLOGICAL ADVANTAGE OF A HIGH MILEAGE TREAD COMPOUND PROVIDES LONGER MILEAGE AND TREAD LIFE FOR THIS HIGH PERFORMING TIRE.

**VANCOCONTACT – EXCELLENT ON AND OFF-ROAD CAPABILITY**  
PRECISE STEERING RESPONSE AND TRACTION ON GRAVEL ROADS, IN SAND AND MODERATE SNOW.

**VANCO 4 SEASON – YEAR-ROUND COMFORT AND DURABILITY**  
UNIQUE GROOVE DESIGN AND TREAD PATTERN IMPROVES RESISTANCE TO HYDROPLANING AND PROTECTS AGAINST SIDEWALL DAMAGE.



	UTQG:	TREAD	TRACTION	TEMP
ALL SIZES	280	A	A	A

**FEATURES:**

**BENEFITS:**

- High mileage tread compound
- Optimized contact patch
- Curbing Rib
- Circumferential but not directionally-oriented tread pattern

- Longer mileage and tread life.
- Improved hydroplaning performance and wet grip.
- Protects sidewall from damage of daily use.
- Enhanced rolling comfort and low tire noise.

**FEATURES:**

**BENEFITS:**

- Flat-Belt-Concept construction
- Straight circumferential and wide lateral grooves
- New compound technology with specifically adapted tread pattern
- Continuous central ribs, fine venting and lateral grooves

- Excellent mileage.
- Provides added resistance to hydroplaning.
- Improved control and braking on wet surfaces.
- Precise steering response and low tire noise.

**FEATURES:**

**BENEFITS:**

- Rounder corners of contact patch blocks
- Solid sidewall curb rib
- Special shoulder groove design and interlocking tread pattern

- Improved resistance against hydroplaning.
- Protection against sidewall damage.
- Increased ride comfort and lower tire noise.



VANCO™ 8

		RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER	TIRE WEIGHT	TIRE WEIGHT (KG)	MAX. INFLATION PRESSURE	OVERALL SECTION WIDTH (MEASURING RIM)	APPROVED RIM WIDTHS	TREAD DEPTH	REVS PER MILE
14			185R14	102/100Q	D	BSW	04514280000	25.6	10.7	23.4	65	7.4 (5.5)	5.0 - 6.0	10/32	817	
			195R14	106/104Q	D	BSW	04514300000	26.2	12.0	26.4	65	7.8 (5.5)	5.0 - 6.0	10/32	797	
			205R14	109/107P	D	BSW	04514360000	27.0	13.1	28.9	65	8.2 (6.0)	5.5 - 6.5	10/32	774	
15	70		195/70R15	104/102R	D	BSW	04514410000	25.8	11.6	25.4	65	7.9 (6.0)	5.0 - 6.0	10/32	811	
			215/70R15	109/107R	D	BSW	04514430000	26.9	13.7	30.2	65	8.7 (6.5)	5.0 - 7.0	10/32	778	
			195/65R16	104/102R	D	BSW	04713260000	26.0	11.8	25.9	65	7.9 (6.0)	5.5 - 6.0	10/32	805	

ORIGINAL EQUIPMENT APPLICATIONS - VANCO™ 8

Mercedes	15	70	195/70R15	104/102R	D	BSW	04514410000	25.8	11.6	25.4	65	7.9 (6.0)	5.0 - 6.0	10/32	811
----------	----	----	-----------	----------	---	-----	-------------	------	------	------	----	-----------	-----------	-------	-----

VANCOCONTACT™

15	65	205/65R15	99T	RF	BSW	04514550000	25.5	9.9	21.7	51	8.2 (6.0)	5.5 - 7.5	10/32	816
16	65	215/65R16	102/100H	C	BSW	04713510000	27.0	13.0	28.5	50	8.7 (6.5)	6.0 - 7.5	11/32	772

VANCO™ 4 SEASON

15	70	195/70R15	104/102R	D	BSW	04574410000	25.7	12.0	26.4	65	7.9 (6.0)	5.0 - 6.0	13/32	810
		225/70R15	112/110R	D	BSW	04574450000	27.4	14.9	32.7	65	9.0 (6.5)	6.0 - 7.0	13/32	761
16	65	205/65R16	107/105T	D	BSW	04733060000	26.5	17.3	38.1	70	8.23 (6.0)	5.5 - 7.5	13/32	787

ORIGINAL EQUIPMENT APPLICATIONS - VANCO™ 4 SEASON

Mercedes	15	70	195/70R15	104/102R	D	BSW	04574410000	25.7	12.0	26.4	65	7.9 (6.0)	5.0 - 6.0	13/32	810
Mercedes			225/70R15	112/110R	C	BSW	04574450000	27.4	14.9	32.7	65	9.0 (6.5)	6.0 - 7.0	13/32	761

VANCO™ 8 / VANCOCONTACT™ / VANCO™ 4 SEASON

ULTRA HIGH PERFORMANCE

PERFORMANCE & TOURING

LIGHT TRUCK & SUV PERFORMANCE

LIGHT TRUCK & SUV LUXURY & COMFORT

VAN

WINTER

# CONTI WINTER CONTACT™ TS810

TAKE HOLD OF THE ROAD IN SNOW CONDITIONS  
ENHANCED ABSORPTION LEADS TO INCREASED TRACTION  
AND HANDLING IN SNOWY CONDITIONS.



MEETS THE SEVERE SNOW SERVICE  
REQUIREMENTS OF THE RUBBER  
MANUFACTURERS ASSOCIATION  
(RMA) AND THE RUBBER  
ASSOCIATION OF CANADA (RAC).

## FEATURES:

- Asymmetrical tread design with sturdy center and inner shoulder blocks
- 20% wider sipes on the inner shoulder
- New sipe spacers prevents sipes from closing during surface contact
- Innovative component compound
- Tailored tread concept: Customized tread design with respect to the width of the tire

## BENEFITS:

- Enhanced grip in snow conditions.
- Enhanced snow absorption.
- Increased traction and handling in snowy conditions.
- Improved performance on wet roads, better driving stability and increased tire tread life.
- Improved wet handling capabilities as more grooves evacuate more water.



# CONTI WINTERCONTACT™ TS810

RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER	TIRE WEIGHT (KG)	TIRE WEIGHT (LB)	MAX. INFLATION PRESSURE	OVERALL SECTION WIDTH (MEASURING RIM)	APPROVED RIM WIDTHS	TREAD DEPTH	REVS PER MILE
15	65	185/65R15	88T	SL	BSW	03533450000	24.5	8.1	17.9	51	7.4 (5.5)	5.0 - 6.5	11/32	849
		195/65R15	95T	XL	BSW	03533770000	25.0	8.3	18.3	51	7.9 (6.0)	5.5 - 7.0	11/32	834
		195/65R15	91H	SL	BSW	03533580000	25.0	8.3	18.3	51	7.9 (6.0)	5.0 - 7.0	11/32	835
		195/65R15	91T	SL	BSW	03533570000	25.0	8.3	18.3	51	7.9 (6.0)	5.0 - 7.0	11/32	835
		195/65R15	91T	SL	BSW	03533240000	25.0	8.4	18.5	51	7.9 (6.0)	5.0 - 7.0	11/32	835
		205/65R15	94T	SL	BSW	03533700000	25.5	10.2	22.3	51	8.2 (6.0)	5.5 - 7.5	11/32	818
	60	205/65R15	94H	SL	BSW	03533530000	25.5	10.2	22.3	51	8.2 (6.0)	5.5 - 7.5	11/32	818
		195/60R15	88H	SL	BSW	03533790000	24.3	8.0	17.5	51	7.9 (6.0)	5.5 - 7.0	10/32	854
		195/60R15	88T	SL	BSW	03533780000	24.2	7.8	17.1	51	7.9 (6.0)	5.0 - 7.0	11/32	856
		205/60R15	91T	SL	BSW	03533760000	24.7	8.6	18.9	51	8.2 (6.0)	5.5 - 7.5	11/32	843
		205/60R15	91H	SL	BSW	03533430000	24.7	8.6	18.9	51	8.2 (6.0)	5.5 - 7.5	11/32	843
		55	195/55R15	85H	SL	BSW	03532750000	23.4	8.1	17.8	51	7.9 (6.0)	5.0 - 7.0	11/32
16	60	205/60R16	96H	XL	BSW	03533670000	25.7	8.7	19.2	51	8.2 (6.0)	5.0 - 7.5	11/32	812
		205/60R16	92H	SL	BSW	03533490000	25.7	8.7	19.2	51	8.2 (6.0)	5.0 - 7.5	11/32	812
		235/60R16	100H	SL	BSW	03533460000	27.1	12.3	27.1	51	9.4 (7.0)	6.5 - 8.5	11/32	769
		185/55R16	87T	XL	BSW	03533710000	24.0	7.8	17.2	51	7.9 (6.0)	5.0 - 7.0	11/32	862
	55	195/55R16	87T	SL	BSW	03533440000	24.4	10.9	23.9	51	7.9 (6.0)	5.5 - 7.0	11/32	850
		205/55R16	91H	SL	BSW	03533800000	24.9	9.2	20.2	51	8.4 (6.5)	5.5 - 7.5	11/32	837
		205/55R16	91H	SL	BSW	03533550000	24.9	9.5	20.8	51	8.4 (6.5)	5.5 - 7.5	11/32	837
		205/55R16	91T	SL	BSW	03533540000	24.9	9.7	21.3	51	8.4 (6.5)	5.5 - 7.5	11/32	837
		215/55R16	97H	XL	BSW	03533850000	25.3	10.5	23.1	51	8.9 (7.0)	6.0 - 7.5	11/32	824
		215/55R16	93H	SL	BSW	03533840000	25.3	10.4	22.9	51	8.9 (7.0)	6.0 - 7.5	11/32	824
		225/55R16	95H	SL	BSW	03533820000	25.7	10.5	23.1	51	9.1 (7.0)	6.0 - 8.0	11/32	810
		225/55R16	99H	XL	BSW	03533680000	25.7	10.9	23.9	51	9.1 (7.0)	6.0 - 8.0	11/32	810
		225/55R16	95H	SL	BSW	03533500000	25.7	10.7	23.5	51	9.1 (7.0)	6.0 - 8.0	11/32	810
		50	225/50R16	93H	SL	BSW	03533870000	24.9	10.4	22.9	51	9.1 (7.0)	6.0 - 8.0	11/32
17	55	225/55R17	97H	SL	BSW	03532760000	26.7	11.2	24.6	51	9.1 (7.0)	6.0 - 8.0	11/32	780
	50	225/50R17	98H	XL	BSW	03533660000	25.9	11.0	24.2	51	9.1 (7.0)	6.0 - 8.0	11/32	806
	45	225/45R17	91H	SL	BSW	03533960000	25.0	10.3	22.7	51	8.9 (7.5)	7.0 - 8.5	11/32	835
		225/45R17	94V	XL	BSW	03533600000	25.0	9.8	21.6	51	8.9 (7.5)	7.0 - 8.5	11/32	835
		225/45R17	91H	SL	BSW	03533590000	25.0	10.2	22.4	51	8.9 (7.5)	7.0 - 8.5	11/32	835
		235/45R17	94H	SL	BSW	03533520000	25.3	10.7	23.5	51	9.3 (8.0)	7.5 - 9.0	11/32	823
		235/45R17	97V	XL	BSW	03532770000	25.3	10.5	23.1	51	9.3 (8.0)	7.0 - 9.0	11/32	823

## SELF-SUPPORTING RUN FLAT TIRES

17	45	225/45R17	91H	SL	BSW	03533390000	25.0	12.0	26.4	51	8.9 (7.5)	7.0 - 8.5	10/32	835
----	----	-----------	-----	----	-----	-------------	------	------	------	----	-----------	-----------	-------	-----

## ORIGINAL EQUIPMENT APPLICATIONS

Mercedes	15	65	185/65R15	88T	SL	BSW	03533450000	24.5	8.1	17.9	51	7.4 (5.5)	5 - 6.5	11/32	849
Volkswagen			195/65R15	95T	XL	BSW	03533770000	25.0	8.3	18.3	51	7.9 (6.0)	5.5 - 7.0	11/32	834
Mercedes			205/65R15	94T	SL	BSW	03533700000	25.5	10.2	22.3	51	8.2 (6.0)	5.5 - 7.5	11/32	818
Mercedes		205/65R15	94H	SL	BSW	03533530000	25.5	10.2	22.3	51	8.2 (6.0)	5.5 - 7.5	11/32	818	
Mercedes		60	205/60R15	91H	SL	BSW	03533430000	24.7	8.6	18.9	51	8.2 (6.0)	5.5 - 7.5	11/32	843
Audi			205/60R16	96H	XL	BSW	03533670000	25.7	8.7	19.2	51	8.2 (6.0)	5.0 - 7.5	11/32	812
Mercedes	205/60R16		92H	SL	BSW	03533490000	25.7	8.7	19.2	51	8.2 (6.0)	5.0 - 7.5	11/32	812	
Volkswagen/Audi	16	60	235/60R16	100H	SL	BSW	03533460000	27.1	12.3	27.1	51	9.4 (7.0)	6.5 - 8.5	11/32	769
Mercedes			195/55R16	87T	SL	BSW	03533440000	24.4	10.9	23.9	51	7.9 (6.0)	5.5 - 7.0	11/32	850
Volkswagen			215/55R16	97H	XL	BSW	03533850000	25.3	10.5	23.1	51	8.9 (7.0)	6.0 - 7.5	11/32	824
Audi		55	215/55R16	93H	SL	BSW	03533840000	25.3	10.4	22.9	51	8.9 (7.0)	6.0 - 7.5	11/32	824
Audi			225/55R16	99H	XL	BSW	03533680000	25.7	10.9	23.9	51	9.1 (7.0)	6.0 - 8.0	11/32	810
Mercedes			225/55R16	95H	SL	BSW	03533500000	25.7	10.7	23.5	51	9.1 (7.0)	6.0 - 8.0	11/32	810
Audi	17	50	225/50R17	98H	XL	BSW	03533660000	25.9	11.0	24.2	51	9.1 (7.0)	6.0 - 8.0	11/32	806
Mercedes			225/45R17	91H	SL	BSW	03533390000	25.0	12.0	26.4	51	8.9 (7.5)	7.0 - 8.5	10/32	835
Mercedes/BMW			235/45R17	94H	SL	BSW	03533520000	25.3	10.7	23.5	51	9.3 (8.0)	7.5 - 9.0	11/32	823

NEW PRODUCT AVAILABLE FALL 2005



# CONTI WINTER CONTACT™ TS810 S

INNOVATIVE COMPONENT TECHNOLOGY ALLOWS FOR INCREASED TRACTION AND STABILITY ON WET AND SNOWY ROADS  
PRECISE HANDLING AND SPORTY PERFORMANCE IN WET CONDITIONS.



MEETS THE SEVERE SNOW SERVICE REQUIREMENTS OF THE RUBBER MANUFACTURERS ASSOCIATION (RMA) AND THE RUBBER ASSOCIATION OF CANADA (RAC).

## FEATURES:

- Rib oriented design
- 20% wider sipes on the inner shoulder
- New sipe spacers prevents sipes from closing during surface contact
- Innovative Component Technology

## BENEFITS:

- More precise handling and sportier performance compared to the TS810.
- Enhanced snow absorption.
- Increased traction and handling in snowy conditions.
- Improved performance on wet roads, better driving stability and increased tire tread life.

# CONTI WINTERCONTACT™ TS810 S

ULTRA HIGH PERFORMANCE

PERFORMANCE & TOURING

LIGHT TRUCK & SUV PERFORMANCE

LIGHT TRUCK & SUV LUXURY & COMFORT

VAN

WINTER

	RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER	TIRE WEIGHT (KG)	TIRE WEIGHT (LB)	MAX. INFLATION PRESSURE	OVERALL SECTION WIDTH (MEASURING RIM)	APPROVED RIM WIDTHS	TREAD DEPTH	REVS PER MILE
16	55	205/55R16	94V	XL	BSW	03533560000	24.9	9.2	20.2	51	8.4 (6.5)	5.5 - 7.5	11/32	837	
		205/55R16	91H	SL	BSW	03532850000	24.9	9.6	21.1	51	8.4 (6.5)	5.5 - 7.5	11/32	837	
		215/55R16	97V	XL	BSW	03533860000	25.3	10.1	22.2	51	8.9 (7.0)	6.0 - 7.5	11/32	824	
		225/55R16	99V	XL	BSW	03533890000	25.7	11.4	25.0	51	9.1 (7.0)	6.0 - 8.0	11/32	810	
		225/55R16	95H	SL	BSW	03532840000	25.7	10.7	23.5	51	9.2 (7.0)	6.0 - 8.0	11/32	810	
17	55	205/55R17	95V	XL	BSW	03533630000	25.9	9.6	21.0	51	8.5 (6.5)	5.5 - 7.5	11/32	806	
		215/55R17	94V	XL	BSW	03532830000	26.3	11.5	25.3	51	8.9 (7.0)	6.0 - 7.5	11/32	792	
		225/55R17	101V	XL	BSW	03533880000	26.7	11.5	25.4	51	9.2 (7.0)	6.0 - 8.0	11/32	780	
		235/55R17	103V	XL	BSW	03533470000	27.2	12.0	26.4	51	9.6 (7.5)	6.5 - 8.5	11/32	767	
		245/55R17	102H	SL	BSW	03533370000	27.6	10.0	22.0	51	9.6 (7.5)	7.0 - 8.5	11/32	755	
	50	235/50R17	100V	XL	BSW	03533640000	26.3	11.5	25.3	51	9.7 (7.5)	6.5 - 8.5	10/32	794	
	45	245/45R17	99V	XL	BSW	03533900000	25.7	10.6	23.3	51	9.6 (8.0)	7.0 - 9.0	11/32	812	
		255/45R17	102V	XL	BSW	03532780000	26.0	12.3	27.1	51	10.0 (8.5)	8.0 - 9.5	11/32	801	
18	45	245/45R18	100V	XL	BSW	03533350000	26.7	11.0	24.2	51	9.6 (8.0)	7.5 - 9.0	11/32	782	
		255/45R18	103V	XL	BSW	03533750000	27.0	11.0	24.2	51	10.0 (8.5)	8.0 - 9.5	11/32	771	
		225/40R18	92V	XL	BSW	03533940000	25.1	9.9	21.8	51	9.1 (8.0)	7.0 - 9.0	11/32	832	
		235/40R18	95V	XL	BSW	03533740000	25.4	10.0	21.9	51	9.5 (8.5)	8.0 - 9.5	11/32	821	
		235/40R18	95V	XL	BSW	03533690000	25.4	10.5	23.1	51	9.5 (8.5)	8.0 - 9.5	11/32	821	
	40	245/40R18	97W	XL	BSW	03533910000	25.7	11.1	24.4	51	9.8 (8.5)	8.0 - 9.5	11/32	811	
		245/40R18	97V	XL	BSW	03533480000	25.7	11.0	24.2	51	9.8 (8.5)	8.0 - 9.5	11/32	811	
		255/40R18	99V	XL	BSW	03533650000	26.0	11.0	24.2	51	10.2 (9.0)	8.5 - 10.0	10/32	801	
		265/40R18	101V	XL	BSW	03533720000	26.3	13.3	29.2	51	10.7 (9.5)	9.0 - 10.0	10/32	791	
		35	255/35R18	94V	XL	BSW	03532790000	25.0	11.0	24.2	51	10.0 (8.5)	8.0 - 9.5	11/32	833
265/35R18	97V		XL	BSW	03532800000	25.3	11.3	24.9	51	10.7 (9.5)	9.0 - 10.0	11/32	824		
19	35	235/35R19	91V	XL	BSW	03533610000	25.5	10.6	23.3	51	9.5 (8.5)	8.0 - 9.5	11/32	818	
		235/35R19	91W	XL	BSW	03532810000	25.5	9.7	21.3	51	9.3 (8.0)	7.5 - 9.0	11/32	818	
		245/35R19	93W	XL	BSW	03533920000	25.8	10.7	23.5	51	9.8 (8.5)	8.0 - 9.5	11/32	810	
	30	275/30R19	96W	XL	BSW	03533930000	25.5	11.9	26.2	51	10.8 (9.5)	9.0 - 10.0	11/32	818	
		295/30R19	100V	XL	BSW	03533620000	26.0	11.0	24.2	51	11.6 (10.5)	10.0 - 11.0	10/32	803	
		295/30R19	100W	XL	BSW	03532820000	26.0	13.6	29.9	51	11.6 (10.5)	10.0 - 11.0	11/32	803	

## SELF-SUPPORTING RUN FLAT TIRES

16	55	195/55R16	87H	SL	BSW	03533730000	24.4	8.7	19.0	51	7.9 (6.0)	5.5 - 7.0	10/32	850
		205/55R16	91H	SL	BSW	03533310000	24.9	10.0	21.9	51	8.4 (6.5)	5.5 - 7.5	11/32	837
17	45	225/45R17	94V	XL	BSW	03533330000	25.0	12.0	26.4	51	8.9 (7.5)	7.0 - 8.5	10/32	835
		225/45R17	91H	SL	BSW	03533320000	25.0	12.0	26.4	51	8.9 (7.5)	7.0 - 8.5	10/32	835
		245/45R17	99V	XL	BSW	03533400000	25.7	10.6	23.3	51	9.6 (8.0)	7.0 - 9.0	10/32	812
		245/45R17	95H	SL	BSW	03533340000	25.7	10.6	23.3	51	9.6 (8.0)	7.0 - 9.0	10/32	812
18	45	245/45R18	100V	XL	BSW	03533420000	26.7	11.0	24.2	51	9.6 (8.0)	7.5 - 9.0	10/32	782

## ORIGINAL EQUIPMENT APPLICATIONS

BMW/Mini	16	55	195/55R16	87H	SL	BSW	03533730000	24.4	8.7	19.0	51	7.9 (6.0)	5.5 - 7.0	10/32	850	
BMW			205/55R16	91H	SL	BSW	03533310000	24.9	10.0	21.9	51	8.4 (6.5)	5.5 - 7.5	11/32	837	
Porsche	17	55	205/55R17	95V	XL	BSW	03533630000	25.9	9.6	21.0	51	8.5 (6.5)	5.5 - 7.5	11/32	806	
BMW			245/55R17	102H	SL	BSW	03533370000	27.6	10.0	22.0	51	9.6 (7.5)	7.0 - 8.5	11/32	755	
Porsche			235/50R17	100V	XL	BSW	03533640000	26.3	11.5	25.3	51	9.7 (7.5)	6.5 - 8.5	10/32	794	
BMW		45	225/45R17	94V	XL	BSW	03533330000	25.0	12.0	26.4	51	8.9 (7.5)	7.0 - 8.5	10/32	835	
BMW			225/45R17	91H	SL	BSW	03533320000	25.0	12.0	26.4	51	8.9 (7.5)	7.0 - 8.5	10/32	835	
Mercedes			245/45R17	99V	XL	BSW	03533400000	25.7	10.6	23.3	51	9.6 (8.0)	7.0 - 9.0	10/32	812	
BMW			245/45R17	95H	SL	BSW	03533340000	25.7	10.6	23.3	51	9.6 (8.0)	7.0 - 9.0	10/32	812	
Mercedes	18	45	245/45R18	100V	XL	BSW	03533420000	26.7	11.0	24.2	51	9.6 (8.0)	7.5 - 9.0	10/32	782	
BMW			245/45R18	100V	XL	BSW	03533350000	26.7	11.0	24.2	51	9.6 (8.0)	7.5 - 9.0	11/32	782	
Mercedes			255/45R18	103V	XL	BSW	03533750000	27.0	11.0	24.2	51	10.0 (8.5)	8.0 - 9.5	11/32	771	
Porsche			40	235/40R18	95V	XL	BSW	03533740000	25.4	10.0	21.9	51	9.5 (8.5)	8.0 - 9.5	11/32	821
Jaguar				235/40R18	95V	XL	BSW	03533690000	25.4	10.5	23.1	51	9.5 (8.5)	8.0 - 9.5	11/32	821
Mercedes				245/40R18	97V	XL	BSW	03533480000	25.7	11.0	24.2	51	9.8 (8.5)	8.0 - 9.5	11/32	811
Porsche				255/40R18	99V	XL	BSW	03533650000	26.0	11.0	24.2	51	10.2 (9.0)	8.5 - 10.0	10/32	801
Porsche				265/40R18	101V	XL	BSW	03533720000	26.3	13.3	29.2	51	10.7 (9.5)	9.0 - 10.0	10/32	791
Porsche		19	35	235/35R19	91V	XL	BSW	03533610000	25.5	10.6	23.3	51	9.5 (8.5)	8.0 - 9.5	11/32	818
Porsche				295/30R19	100V	XL	BSW	03533620000	26.0	11.0	24.2	51	11.6 (10.5)	10.0 - 11.0	10/32	803

NEW PRODUCT AVAILABLE FALL 2005

# CONTI 4x4 WINTERCONTACT™

## DESIGNED FOR SEVERE WINTER CONDITIONS

THE ADVANCED DESIGN OF THIS TIRE PROVIDES OPTIMUM TRACTION, HANDLING AND WEAR IN EVEN THE HARSHTEST SNOW AND ICE CONDITIONS.



MEETS THE SEVERE SNOW SERVICE REQUIREMENTS OF THE RUBBER MANUFACTURERS ASSOCIATION (RMA) AND THE RUBBER ASSOCIATION OF CANADA (RAC).

### FEATURES:

- Progressive interlocking sipes
- Asymmetrical tread design
- Mountain/snowflake designation
- H, T, and V speed rated

### BENEFITS:

- Provides maximum biting edges for traction.
- Optimum traction, handling, and wear.
- Designed for severe snow, ice and winter conditions.
- Rated for speeds up to 118 mph/190 kph (T), 130 mph/209 kph (H) and 150 mph/240 kph (V).



# CONTI 4x4 WINTERCONTACT™

	RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER	TIRE WEIGHT (KG)	TIRE WEIGHT (LB)	MAX. INFLATION PRESSURE	OVERALL SECTION WIDTH (MEASURING RIM)	APPROVED RIM WIDTHS	TREAD DEPTH	REVS PER MILE
15	80	195/80R15	96T	SL	BSW	03546160000	27.8	10.9	24.0	51	8.0 (5.5)	5.5 - 6.5	12/32	764	
	75	235/75R15	109T	XL	BSW	15467760000	28.9	14.2	31.3	51	9.3 (6.5)	6.0 - 8.0	12/32	720	
	70	205/70R15	96T	SL	BSW	03547000000	25.6	9.9	21.7	51	8.5 (6.0)	5.0 - 7.0	12/32	793	
		265/70R15	112T	SL	BSW	15467770000	30.2	15.4	33.9	51	11.1 (8.0)	7.0 - 9.0	12/32	710	
16	75	225/75R16	104T	SL	BSW	15467840000	29.3	14.1	30.9	51	8.8 (6.0)	6.0 - 7.5	12/32	733	
	70	225/70R16	102H	SL	BSW	03547070000	28.4	13.2	29.1	51	9.0 (6.5)	6.0 - 7.5	12/32	732	
		235/70R16	106T	SL	BSW	03547080000	29.0	14.0	30.8	51	9.4 (7.5)	6.0 - 8.0	12/32	742	
		245/70R16	107T	SL	BSW	03546340000	29.5	14.3	31.4	51	9.8 (7.0)	6.5 - 8.0	12/32	703	
		265/70R16	112T	SL	BSW	03546350000	30.6	16.6	36.6	51	8.6 (8.0)	7.0 - 9.0	12/32	678	
	65	215/65R16	98T	SL	BSW	03536430000	27.0	11.0	24.1	51	8.7 (8.0)	7.0 - 9.0	12/32	770	
255/65R16	109T	SL	BSW	15467780000	29.6	15.5	34.1	51	10.6 (7.5)	7.0 - 9.0	12/32	716			
17	65	235/65R17	108H	XL	BSW	03546230000	29.1	15.4	33.9	51	9.4 (7.0)	6.5 - 8.5	12/32	716	
		235/65R17	104H	SL	BSW	03536890000	29.1	15.5	34.1	51	10.0 (7.0)	6.5 - 8.5	12/32	742	
		265/65R17	112T	SL	BSW	03546450000	30.6	15.4	33.9	51	10.7 (8.0)	7.5 - 9.5	12/32	682	
	60	215/60R17	96H	SL	BSW	03547680000	27.6	9.7	21.3	51	9.1 (6.5)	6.0 - 7.5	12/32	767	
		255/60R17	106H	SL	BSW	03547210000	29.1	14.3	31.5	51	10.2 (6.5)	6.0 - 8.0	12/32	715	
	55	225/55R17	97H	SL	BSW	03547230000	26.8	11.2	24.5	51	9.2 (7.0)	6.0 - 8.0	12/32	776	
		235/55R17	99H	SL	BSW	03547700000	27.2	12.8	28.2	51	9.7 (7.5)	6.0 - 8.5	12/32	767	
275/55R17	109H	SL	BSW	03546460000	29.4	15.4	33.9	51	11.6 (8.5)	7.5 - 9.5	12/32	721			
18	55	255/55R18	105H	SL	BSW	03546260000	29.0	15.3	33.7	51	10.4 (7.0)	6.0 - 8.0	12/32	715	
		255/55R18	109V	XL	BSW	03545530000	29.0	15.5	34.1	51	10.4 (7.0)	6.0 - 8.0	12/32	719	
	50	235/50R18	97H	SL	BSW	03545310000	27.7	11.1	24.3	51	10.0 (7.5)	6.5 - 8.5	12/32	764	
19	50	255/50R19	107V	XL	BSW	03546490000	29.3	15.3	33.7	51	10.4 (8.0)	7.0 - 9.0	12/32	712	
20	40	275/40R20	106V	XL	BSW	03545500000	29.0	15.0	33.0	51	11.4 (9.5)	9.0 - 11.0	12/32	726	
		295/40R20	110V	XL	BSW	03545610000	29.7	15.8	34.8	51	12.3 (10.5)	10.0 - 11.5	12/32	712	

## ORIGINAL EQUIPMENT APPLICATIONS

Ford	15	70	265/70R15	112T	SL	BSW	15467770000	30.2	15.4	33.9	51	11.1 (8.0)	7.0 - 9.0	12/32	710
Porsche	17	65	235/65R17	108H	XL	BSW	03546230000	29.1	15.4	33.9	51	9.4 (7.0)	6.5 - 8.5	12/32	716
		60	215/60R17	96H	SL	BSW	03547680000	27.6	9.7	21.3	51	9.1 (6.5)	6.0 - 7.5	12/32	767
Porsche	18	55	255/55R18	109V	XL	BSW	03545530000	29.0	15.5	34.1	51	10.4 (7.0)	6.0 - 8.0	12/32	719
BMW		50	235/50R18	97H	SL	BSW	03545310000	27.7	11.1	24.3	51	10 (7.5)	6.5 - 8.5	12/32	764
Porsche	19	50	255/50R19	107V	XL	BSW	03546490000	29.3	15.3	33.7	51	10.4 (8.0)	7.0 - 9.0	12/32	712

ULTRA HIGH PERFORMANCE

PERFORMANCE & TOURING

LIGHT TRUCK & SUV PERFORMANCE

LIGHT TRUCK & SUV LUXURY & COMFORT

VAN

WINTER



## EXCELLENT TRACTION AND MOBILITY IN ALL WINTER DRIVING CONDITIONS

THIS TIRE FEATURES OUTSTANDING TRACTION AND SHORTER BRAKING DISTANCE ON BOTH SNOW AND ICE.



UTQG:	TREAD	TRACTION	TEMPERATURE
ALL SIZES	280	A	A

### FEATURES:

- Funnel-shaped tread grooves
- New flat contour and wider tread
- High sipe density and increased number of tread lugs
- Curbing rib

### BENEFITS:

- Excellent hydroplaning resistance.
- Provides increased cornering and mileage performance.
- Outstanding traction and shorter braking distances on snow, ice and wet conditions.
- Protection against sidewall damage.

		RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER	TIRE WEIGHT (KG)	TIRE WEIGHT (LB)	MAX. INFLATION PRESSURE	OVERALL SECTION WIDTH (MEASURING RIM)	APPROVED RIM WIDTHS	TREAD DEPTH	REVS PER MILE
15	70	195/70R15	104/102R	D	BSW	04574330000	25.8	12.0	26.4	65	7.9 (6.0)	5.0 - 6.0	14/32	811		
		225/70R15	112/110R	D	BSW	04574350000	27.4	14.9	32.7	65	9.0 (6.5)	6.0 - 7.0	14/32	762		
16	65	205/65R16	107/105T	D	BSW	04733040000	26.5	13.1	28.8	70	8.23 (6.0)	5.5 - 7.5	14/32	787		

### ORIGINAL EQUIPMENT APPLICATIONS

Mercedes	15	70	195/70R15	104/102R	D	BSW	04574330000	25.8	12.0	26.4	65	7.9 (6.0)	5.0 - 6.0	14/32	811
Mercedes			225/70R15	112/110R	D	BSW	04574350000	27.4	14.9	32.7	65	9.0 (6.5)	6.0 - 7.0	14/32	762

VANGOWINTER™

ULTRA HIGH PERFORMANCE

PERFORMANCE & TOURING

LIGHT TRUCK & SUV PERFORMANCE

LIGHT TRUCK & SUV LUXURY & COMFORT

VAN

WINTER

[WWW.CONTINENTALTIRE.COM](http://WWW.CONTINENTALTIRE.COM)

CONTINENTAL TIRE NORTH AMERICA, INC.

1800 CONTINENTAL BOULEVARD

CHARLOTTE, NORTH CAROLINA 28273