

# VANCO™ 8 / VANCOCONTACT™ / VANCO™ 4 SEASON

**VANCO 8 – OPTIMIZED FUEL ECONOMY AND EXTENDED TREAD LIFE**  
THE TECHNOLOGICAL ADVANTAGE OF A HIGH MILEAGE TREAD COMPOUND PROVIDES LONGER MILEAGE AND TREAD LIFE FOR THIS HIGH PERFORMING TIRE.

**VANCOCONTACT – EXCELLENT ON AND OFF-ROAD CAPABILITY**  
PRECISE STEERING RESPONSE AND TRACTION ON GRAVEL ROADS, IN SAND AND MODERATE SNOW.

**VANCO 4 SEASON – YEAR-ROUND COMFORT AND DURABILITY**  
UNIQUE GROOVE DESIGN AND TREAD PATTERN IMPROVES RESISTANCE TO HYDROPLANING AND PROTECTS AGAINST SIDEWALL DAMAGE.



UTQG: TREAD TRACTION TEMP  
ALL SIZES 280 A A

**FEATURES:**

**BENEFITS:**

- High mileage tread compound
- Optimized contact patch
- Curbing Rib
- Circumferential but not directionally-oriented tread pattern

- Longer mileage and tread life.
- Improved hydroplaning performance and wet grip.
- Protects sidewall from damage of daily use.
- Enhanced rolling comfort and low tire noise.

**FEATURES:**

**BENEFITS:**

- Flat-Belt-Concept construction
- Straight circumferential and wide lateral grooves
- New compound technology with specifically adapted tread pattern
- Continuous central ribs, fine venting and lateral grooves

- Excellent mileage.
- Provides added resistance to hydroplaning.
- Improved control and braking on wet surfaces.
- Precise steering response and low tire noise.

**FEATURES:**

**BENEFITS:**

- Rounder corners of contact patch blocks
- Solid sidewall curb rib
- Special shoulder groove design and interlocking tread pattern

- Improved resistance against hydroplaning.
- Protection against sidewall damage.
- Increased ride comfort and lower tire noise.



VANCO™ 8

		RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER	TIRE WEIGHT	TIRE WEIGHT (KG)	MAX. INFLATION PRESSURE	OVERALL SECTION WIDTH (MEASURING RIM)	APPROVED RIM WIDTHS	TREAD DEPTH	REVS PER MILE
14			185R14	102/100Q	D	BSW	04514280000	25.6	10.7	23.4	65	7.4 (5.5)	5.0 - 6.0	10/32	817	
			195R14	106/104Q	D	BSW	04514300000	26.2	12.0	26.4	65	7.8 (5.5)	5.0 - 6.0	10/32	797	
			205R14	109/107P	D	BSW	04514360000	27.0	13.1	28.9	65	8.2 (6.0)	5.5 - 6.5	10/32	774	
15	70		195/70R15	104/102R	D	BSW	04514410000	25.8	11.6	25.4	65	7.9 (6.0)	5.0 - 6.0	10/32	811	
			215/70R15	109/107R	D	BSW	04514430000	26.9	13.7	30.2	65	8.7 (6.5)	5.0 - 7.0	10/32	778	
	65		195/65R16	104/102R	D	BSW	04713260000	26.0	11.8	25.9	65	7.9 (6.0)	5.5 - 6.0	10/32	805	

ORIGINAL EQUIPMENT APPLICATIONS - VANCO™ 8

Mercedes	15	70	195/70R15	104/102R	D	BSW	04514410000	25.8	11.6	25.4	65	7.9 (6.0)	5.0 - 6.0	10/32	811
----------	----	----	-----------	----------	---	-----	-------------	------	------	------	----	-----------	-----------	-------	-----

VANCOCONTACT™

15	65	205/65R15	99T	RF	BSW	04514550000	25.5	9.9	21.7	51	8.2 (6.0)	5.5 - 7.5	10/32	816
16	65	215/65R16	102/100H	C	BSW	04713510000	27.0	13.0	28.5	50	8.7 (6.5)	6.0 - 7.5	11/32	772

VANCO™ 4 SEASON

15	70	195/70R15	104/102R	D	BSW	04574410000	25.7	12.0	26.4	65	7.9 (6.0)	5.0 - 6.0	13/32	810
		225/70R15	112/110R	D	BSW	04574450000	27.4	14.9	32.7	65	9.0 (6.5)	6.0 - 7.0	13/32	761
16	65	205/65R16	107/105T	D	BSW	04733060000	26.5	17.3	38.1	70	8.23 (6.0)	5.5 - 7.5	13/32	787

ORIGINAL EQUIPMENT APPLICATIONS - VANCO™ 4 SEASON

Mercedes	15	70	195/70R15	104/102R	D	BSW	04574410000	25.7	12.0	26.4	65	7.9 (6.0)	5.0 - 6.0	13/32	810
Mercedes			225/70R15	112/110R	C	BSW	04574450000	27.4	14.9	32.7	65	9.0 (6.5)	6.0 - 7.0	13/32	761

VANCO™ 8 / VANCOCONTACT™ / VANCO™ 4 SEASON

ULTRA HIGH PERFORMANCE

PERFORMANCE & TOURING

LIGHT TRUCK & SUV PERFORMANCE

LIGHT TRUCK & SUV LUXURY & COMFORT

VAN

WINTER

# CONTI 4x4 WINTERCONTACT™

## DESIGNED FOR SEVERE WINTER CONDITIONS

THE ADVANCED DESIGN OF THIS TIRE PROVIDES OPTIMUM TRACTION, HANDLING AND WEAR IN EVEN THE HARSHTEST SNOW AND ICE CONDITIONS.



MEETS THE SEVERE SNOW SERVICE REQUIREMENTS OF THE RUBBER MANUFACTURERS ASSOCIATION (RMA) AND THE RUBBER ASSOCIATION OF CANADA (RAC).

### FEATURES:

- Progressive interlocking sipes
- Asymmetrical tread design
- Mountain/snowflake designation
- H, T, and V speed rated

### BENEFITS:

- Provides maximum biting edges for traction.
- Optimum traction, handling, and wear.
- Designed for severe snow, ice and winter conditions.
- Rated for speeds up to 118 mph/190 kph (T), 130 mph/209 kph (H) and 150 mph/240 kph (V).

# CONTI 4x4 WINTERCONTACT™

	RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER	TIRE WEIGHT (KG)	TIRE WEIGHT (LB)	MAX. INFLATION PRESSURE	OVERALL SECTION WIDTH (MEASURING RIM)	APPROVED RIM WIDTHS	TREAD DEPTH	REVS PER MILE
15	80	195/80R15	96T	SL	BSW	03546160000	27.8	10.9	24.0	51	8.0 (5.5)	5.5 - 6.5	12/32	764	
	75	235/75R15	109T	XL	BSW	15467760000	28.9	14.2	31.3	51	9.3 (6.5)	6.0 - 8.0	12/32	720	
	70	205/70R15	96T	SL	BSW	03547000000	25.6	9.9	21.7	51	8.5 (6.0)	5.0 - 7.0	12/32	793	
		265/70R15	112T	SL	BSW	15467770000	30.2	15.4	33.9	51	11.1 (8.0)	7.0 - 9.0	12/32	710	
16	75	225/75R16	104T	SL	BSW	15467840000	29.3	14.1	30.9	51	8.8 (6.0)	6.0 - 7.5	12/32	733	
	70	225/70R16	102H	SL	BSW	03547070000	28.4	13.2	29.1	51	9.0 (6.5)	6.0 - 7.5	12/32	732	
		235/70R16	106T	SL	BSW	03547080000	29.0	14.0	30.8	51	9.4 (7.5)	6.0 - 8.0	12/32	742	
		245/70R16	107T	SL	BSW	03546340000	29.5	14.3	31.4	51	9.8 (7.0)	6.5 - 8.0	12/32	703	
		265/70R16	112T	SL	BSW	03546350000	30.6	16.6	36.6	51	8.6 (8.0)	7.0 - 9.0	12/32	678	
	65	215/65R16	98T	SL	BSW	03536430000	27.0	11.0	24.1	51	8.7 (8.0)	7.0 - 9.0	12/32	770	
255/65R16	109T	SL	BSW	15467780000	29.6	15.5	34.1	51	10.6 (7.5)	7.0 - 9.0	12/32	716			
17	65	235/65R17	108H	XL	BSW	03546230000	29.1	15.4	33.9	51	9.4 (7.0)	6.5 - 8.5	12/32	716	
		235/65R17	104H	SL	BSW	03536890000	29.1	15.5	34.1	51	10.0 (7.0)	6.5 - 8.5	12/32	742	
		265/65R17	112T	SL	BSW	03546450000	30.6	15.4	33.9	51	10.7 (8.0)	7.5 - 9.5	12/32	682	
	60	215/60R17	96H	SL	BSW	03547680000	27.6	9.7	21.3	51	9.1 (6.5)	6.0 - 7.5	12/32	767	
		255/60R17	106H	SL	BSW	03547210000	29.1	14.3	31.5	51	10.2 (6.5)	6.0 - 8.0	12/32	715	
	55	225/55R17	97H	SL	BSW	03547230000	26.8	11.2	24.5	51	9.2 (7.0)	6.0 - 8.0	12/32	776	
		235/55R17	99H	SL	BSW	03547700000	27.2	12.8	28.2	51	9.7 (7.5)	6.0 - 8.5	12/32	767	
275/55R17	109H	SL	BSW	03546460000	29.4	15.4	33.9	51	11.6 (8.5)	7.5 - 9.5	12/32	721			
18	55	255/55R18	105H	SL	BSW	03546260000	29.0	15.3	33.7	51	10.4 (7.0)	6.0 - 8.0	12/32	715	
		255/55R18	109V	XL	BSW	03545530000	29.0	15.5	34.1	51	10.4 (7.0)	6.0 - 8.0	12/32	719	
	50	235/50R18	97H	SL	BSW	03545310000	27.7	11.1	24.3	51	10.0 (7.5)	6.5 - 8.5	12/32	764	
19	50	255/50R19	107V	XL	BSW	03546490000	29.3	15.3	33.7	51	10.4 (8.0)	7.0 - 9.0	12/32	712	
20	40	275/40R20	106V	XL	BSW	03545500000	29.0	15.0	33.0	51	11.4 (9.5)	9.0 - 11.0	12/32	726	
		295/40R20	110V	XL	BSW	03545610000	29.7	15.8	34.8	51	12.3 (10.5)	10.0 - 11.5	12/32	712	

## ORIGINAL EQUIPMENT APPLICATIONS

Ford	15	70	265/70R15	112T	SL	BSW	15467770000	30.2	15.4	33.9	51	11.1 (8.0)	7.0 - 9.0	12/32	710
Porsche	17	65	235/65R17	108H	XL	BSW	03546230000	29.1	15.4	33.9	51	9.4 (7.0)	6.5 - 8.5	12/32	716
BMW		60	215/60R17	96H	SL	BSW	03547680000	27.6	9.7	21.3	51	9.1 (6.5)	6.0 - 7.5	12/32	767
Porsche	18	55	255/55R18	109V	XL	BSW	03545530000	29.0	15.5	34.1	51	10.4 (7.0)	6.0 - 8.0	12/32	719
BMW		50	235/50R18	97H	SL	BSW	03545310000	27.7	11.1	24.3	51	10 (7.5)	6.5 - 8.5	12/32	764
Porsche	19	50	255/50R19	107V	XL	BSW	03546490000	29.3	15.3	33.7	51	10.4 (8.0)	7.0 - 9.0	12/32	712

ULTRA HIGH PERFORMANCE

PERFORMANCE & TOURING

LIGHT TRUCK & SUV PERFORMANCE

LIGHT TRUCK & SUV LUXURY & COMFORT

VAN

WINTER



## EXCELLENT TRACTION AND MOBILITY IN ALL WINTER DRIVING CONDITIONS

THIS TIRE FEATURES OUTSTANDING TRACTION AND SHORTER BRAKING DISTANCE ON BOTH SNOW AND ICE.



UTQG:	TREAD	TRACTION	TEMPERATURE
ALL SIZES	280	A	A

### FEATURES:

- Funnel-shaped tread grooves
- New flat contour and wider tread
- High sipe density and increased number of tread lugs
- Curbing rib

### BENEFITS:

- Excellent hydroplaning resistance.
- Provides increased cornering and mileage performance.
- Outstanding traction and shorter braking distances on snow, ice and wet conditions.
- Protection against sidewall damage.

		RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER	TIRE WEIGHT (KG)	TIRE WEIGHT (LB)	MAX. INFLATION PRESSURE	OVERALL SECTION WIDTH (MEASURING RIM)	APPROVED RIM WIDTHS	TREAD DEPTH	REVS PER MILE
15	70	195/70R15	104/102R	D	BSW	04574330000	25.8	12.0	26.4	65	7.9 (6.0)	5.0 - 6.0	14/32	811		
		225/70R15	112/110R	D	BSW	04574350000	27.4	14.9	32.7	65	9.0 (6.5)	6.0 - 7.0	14/32	762		
16	65	205/65R16	107/105T	D	BSW	04733040000	26.5	13.1	28.8	70	8.23 (6.0)	5.5 - 7.5	14/32	787		

### ORIGINAL EQUIPMENT APPLICATIONS

Mercedes	15	70	195/70R15	104/102R	D	BSW	04574330000	25.8	12.0	26.4	65	7.9 (6.0)	5.0 - 6.0	14/32	811
Mercedes			225/70R15	112/110R	D	BSW	04574350000	27.4	14.9	32.7	65	9.0 (6.5)	6.0 - 7.0	14/32	762

VANGOWINTER™

ULTRA HIGH PERFORMANCE

PERFORMANCE & TOURING

LIGHT TRUCK & SUV PERFORMANCE

LIGHT TRUCK & SUV LUXURY & COMFORT

VAN

WINTER