

Closet Shelf

Submitted by **Ray Wilkes** (raydad@prodigy.net) September 2004

Add a shelf to the lower section of the clothes closet.



APPROX. MODIFICATION TIME: 1 hour

PART LIST

All prices are pre tax.

See current TechRally Schedule for availability and price of ModKit.

Plywood 5/8" thick, 21 1/2" square,	\$2
Shelf supports, 4	\$2
Fabric, carpet tape	\$1
APPROX. TOTAL COST OF PARTS	≈ \$5

TOOLS

Drill

INSTRUCTIONS

- Build a shelf of 5/8" thick plywood, 21 1/2" square, with a 6 3/4" long notch in the forward left corner to fit the piece of thin plywood Winnebago used around the vent pipe.
- Drill 1/4" holes in the forward and aft walls. These holes are located 7" above the original floor, and at 6" and 16 1/4" out from the back wall, on each of the forward and aft walls.
- Fit in the 4 plastic brackets. Hold these supports in with masking tape to make it easier to slide the shelf down.



The shelf removed to show where I placed the plastic supports, and how the 15-quart boxes and dust buster fit in below the shelf.

- To finish off the shelf, put some plain colored fabric over the top and edges, and fastened it to the underside of the shelf with carpet tape.



The existing clothes rod is raised 3"

- The clothes rods seem to be located at different distances from the ceiling, and in some Rialtas it is helpful to raise the rod just high enough to still be able to place hangers over the rod.

Updated
Tuesday, September 28, 2004